

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

### Web Services API Reference

CometD notifications

## CometD notifications

You can subscribe to the /v2/me/openmedia topic to receive CometD notifications for the Open Media API. This topic provides messages related to OpenMedia interactions, including changes to OpenMedia interaction state and updates to OpenMedia interaction data. It supports the following message types:

OpenmediaStateChangeMessage

#### OpenmediaStateChangeMessage

Property	Description
data	The data element is present in all CometD notifications and is the root JSON element. You can use data.messageType to identify the message and determine what other properties should be present.
data.messageType	This property identifies the message type, in this case OpenmediaStateChangeMessage.
data.notificationType	This property further identifies the type of notification and can have one of the following values:
	<ul> <li>StatusChange — The status of the openmedia interaction has changed.</li> </ul>
	<ul> <li>PropertiesUpdated — The openmedia data has changed.</li> </ul>
	<ul> <li>Error — This is sent when an operation on the openmedia resource fails.</li> </ul>
data.openmedia	An openmedia resource with the updated state and capabilities.
data.referenceId	The reference identifier is used to link the notification to the original request that created it.

#### Example

```
{
    "data":{
        "openmedia":{
            "state":"Processing",
            "capabilities":[
            "Transfer",
            "AttachUserData",
            "UpdateUserData",
            "DeleteUserData",
            "SetInFocus",
            "Complete"
```