



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services and Applications Deployment Guide

Deploying the web application for 8.5.201.09 or earlier

Deploying the web application for 8.5.201.09 or earlier

Important

Complete the steps on this page if you're installing Web Services and Applications version 8.5.201.09 or earlier; otherwise, go to [Deploying the web application](#).

The Web Services web application uses the Jetty root context. If other web applications served by the same instance of Jetty also use the root context, this can prevent the Web Services web application from getting routed requests. If you are working with a fresh install of Jetty, you should remove the default Jetty files from the **\$JETTY_HOME/webapps** and **\$JETTY_HOME/contexts** folders.

Complete the following steps for each Web Services node.

Start

1. Stop Jetty.
2. Copy the **jetty.xml** file from *installation_CD/jetty* to **\$JETTY_HOME/etc**.
3. Copy the **cloud-web.xml** file from *installation_CD/jetty* to **\$JETTY_HOME/webapps**.
4. Copy the **logback.xml** file from *installation_CD/jetty* to **\$JETTY_HOME/resources**.
5. Copy the **cloud-web.war** file from *installation_CD/webapp* to **\$JETTY_HOME/webapps**.
6. Copy the configuration files from *installation_CD/conf* to a local folder of your choosing. For example, **\$JETTY_HOME/genconfig**.

End

Next Step

- [Configuring Web Services for 8.5.201.09 or earlier](#)