



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

Toast and case data

5/4/2025

Toast and case data

This is part of the [API Basics](#) section of the [Web Services API](#).

Contents

- [1 Toast and case data](#)
 - [1.1 Overview](#)
 - [1.2 Toast Data](#)
 - [1.3 Case Data](#)

Overview

Web Services provides two different optional filtered subsets of the data found in the `userData` property of the call resource. Toast data is intended to be used for screen-pop (or "toast") and is included for ringing or dialing calls. Case data is included for established calls and is intended to represent the business-relevant subset of data included on the call.

The set of data that is included in the toast and case properties of the call resource are configured using the `toast-filter` and `case-filter` voice settings.

In addition to the key and value properties entries in the toast and case properties include the `displayName` property configured in the filter. The overall intention is to provide API users all the information required to build a toast/popup and/or call data display without having to manage filtering and metadata on their own.

See the sections below for examples of configuring the `toast-filter` and `case-filter` settings as well as call resource examples that include the toast and case properties.

Tip

The `userData` property of the call resource will always contain the full set of data related to the call, regardless of whether a toast/case filter has been configured.

Toast Data

Toast data is intended to support screen pop or "toast" UI elements that alert the agent to a new call. Any desired set of toast data can be configured using the `toast-filter` setting. It is common to configure a minimal subset of the business data to allow the agent to see the information required to greet the customer.

If a `toast-filter` is configured, the toast property is provided on the call resource when a call is in the Ringing or Dialing state.

Examples

[+] Reading voice settings

Request:

```
GET http://127.0.0.1:8080/api/v2/settings/voice
Response:
{ "key" : "name",
  "settings" : [ { "name" : "case-filter",
                  "value" : [ { "attachedDataKey" : "CustomerName",
                              "displayName" : "Customer"
                            } ]
                } ]
}
```

```
    },
    { "attachedDataKey" : "POC",
      "displayName" : "Purpose of Call"
    }
  ],
  { "name" : "toast-filter",
    "value" : [ { "attachedDataKey" : "CustomerName",
                  "displayName" : "Customer"
                } ]
  }
],
"statusCode" : 0
}
```

[+] Setting a toast-filter

Request

```
POST /api/v2/settings/voice
{
  "name": "toast-filter",
  "value": [
    {
      "attachedDataKey": "CustomerName",
      "displayName": "Customer"
    }
  ]
}
```

Response

```
{ "statusCode" : 0 }
```

[+] Notification

```
{
  "data": {
    "messageType": "CallStateChangeMessage",
    "notificationType": "StatusChange",
    "call": {
      "id": "01N0SKNPB8AT3D4MUTCJ82LAES000120",
      "connId": "0072026cb98d140f",
      "state": "Ringing",
      "callUuid": "01A4HVK9AG9CP40B04000VTAES00001A",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/d41b41c3-33fa-4051-a650-511c6a2e2131",
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/0071023c62a4a02a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5005",
          "phoneNumber": "5005",
          "digits": "5005"
        }
      ],
      "dnis": "5000",
    }
  }
}
```

```

    "callType": "Internal",
    "capabilities": [
      "DeleteUserDataPair",
      "AttachUserData",
      "Answer",
      "DeleteUserData",
      "UpdateUserData",
      "StartCallRecording"
    ],
    "userData": {
      "POC": "New Service",
      "CustomerName": "Chris"
    },
    "toast": [
      {
        "key": "CustomerName",
        "displayName": "Customer",
        "value": "Chris"
      }
    ],
    "duration": "0",
    "mute": "Off",
    "recordingState": "Stopped",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "monitoring": false
  },
  "phoneNumber": "5000"
},
"channel": "/v2/me/calls"
}

```

Case Data

Case data is intended to provide a business-relevant set of call data that API developers can use to populate a call data user interface. Case data is only provided after the agent has accepted the call and it is in the Established state. The set of userData to be included in the case property can be configured via the case-filter setting as shown in the examples below.

Examples

[+] Setting a case-filter

Request

```

POST /api/v2/settings/voice
{
  "name": "case-filter",
  "value": [
    {
      "attachedDataKey": "CustomerName",
      "displayName": "Customer"
    },
    {
      "attachedDataKey": "POC",
      "displayName": "Purpose of Call"
    }
  ]
}

```

```
}
```

Response

```
{ "statusCode" : 0 }
```

Notification

```
{
  "data": {
    "messageType": "CallStateChangeMessage",
    "notificationType": "StatusChange",
    "call": {
      "id": "01N0SKNPB8AT3D4MUTCJ82LAES000120",
      "connId": "0072026cb98d140f",
      "state": "Established",
      "callUuid": "01A4HVK9AG9CP40B04000VTAES00001A",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/
d41b41c3-33fa-4051-a650-511c6a2e2131",
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/0071023c62a4a02a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5005",
          "phoneNumber": "5005",
          "digits": "5005"
        }
      ],
      "dnis": "5000",
      "callType": "Internal",
      "capabilities": [
        "DeleteUserDataPair",
        "SingleStepTransfer",
        "AttachUserData",
        "Hold",
        "InitiateTransfer",
        "Hangup",
        "InitiateConference",
        "DeleteUserData",
        "SingleStepConference",
        "UpdateUserData",
        "SendDtmf",
        "StartCallRecording"
      ],
      "userData": {
        "POC": "New Service",
        "CustomerName": "Chris"
      },
      "duration": "4",
      "mute": "Off",
      "recordingState": "Stopped",
      "supervisorListeningIn": false,
      "monitoredUserMuted": false,
      "monitoring": false,
      "case": [
        {
          "key": "CustomerName",
          "displayName": "Customer",
          "value": "Chris"
        },
        {
          "key": "POC",
```

```
        "displayName": "Purpose of Call",  
        "value": "New Service"  
      }  
    ],  
    },  
    "phoneNumber": "5000"  
  },  
  "channel": "/v2/me/calls"  
}
```