



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Web Edition Developer's Guide and API Reference

Interaction Namespace

Interaction Namespace

Contents

- [1 Interaction Namespace](#)
 - [1.1 Methods](#)
 - [1.2 Type Definitions](#)

Methods

The Interaction namespace includes the following methods:

- [deleteUserData](#)
- [getByInteractionId](#)
- [getInteractions](#)
- [selectCaseByCaseId](#)
- [setUserData](#)
- [markdone](#)
- [blockMarkdone](#)
- [unblockMarkdone](#)

deleteUserData

Signature	<static> deleteUserData(<i>interactionId</i> , <i>key</i>)											
Description	Deletes the user data attached to the interaction. The service-client-api.user-data.write-allowed option might restrict the allowed key/value pairs.											
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique identifier for the interaction.</td> </tr> <tr> <td>key</td> <td>string</td> <td>The key to delete from the attached data.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique identifier for the interaction.	key	string	The key to delete from the attached data.		
Name	Type	Description										
interactionId	string	The unique identifier for the interaction.										
key	string	The key to delete from the attached data.										

getByInteractionId

Signature	<static> getByInteractionId(<i>interactionId</i>) → { interaction.Interaction }								
Description	Gets an interaction by its unique identifier.								
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique identifier for the interaction.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique identifier for the interaction.		
Name	Type	Description							
interactionId	string	The unique identifier for the interaction.							

Signature	<static> getByInteractionId(<i>interactionId</i>) → { <i>interaction.Interaction</i> }
Returns	<i>interaction.Interaction</i> or null if the interaction doesn't exist.

getInteractions

Signature	<static> getInteractions() → {Array.< <i>interaction.Interaction</i> >}
Description	Gets all the interactions.
Returns	Array.< <i>interaction.Interaction</i> >

selectCaseByCaseId

Signature	<static> genesys.wwe.service.interaction.selectCaseByCaseId(<i>caseId</i> , <i>succeeded</i> , <i>failed</i>)
Description	<p>Select the case in the UI by case identifier. If you subscribe to the "interaction" events (genesys.wwe.service.subscribe(["interaction"], eventHandler, this);), you will receive the following event:</p> <pre>Received interaction event: { "event": "interaction", "data": { "eventType": "CASE_COLLAPSED", "selectedCaseId": "4401820b- c4e6-4994-69c2-6ae7fdb4905" }, "userAgent": "WWE Server", "protocolVersion": 2 } Received interaction event: { "event": "interaction", "data": { "eventType": "CASE_EXPANDED", "selectedCaseId": "4401820b- c4e6-4994-69c2-6ae7fdb4905" }, "userAgent": "WWE Server", "protocolVersion": 2 } Received interaction event: { "event": "interaction", "data": { "eventType": "CASE_SELECTED", "selectedCaseId": "d4187b87-9fe1-4db8-0515-6a91e666e22d" }, "userAgent": "WWE Server",</pre>

Signature	<static> genesys.wwe.service.interaction.selectCaseByCaselId(caselId, succeeded, failed)								
	<pre> "protocolVersion": 2 } </pre>								
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>caselId</td> <td>string</td> <td>The unique identifier for the case.</td> </tr> </tbody> </table>	Name	Type	Description	caselId	string	The unique identifier for the case.		
Name	Type	Description							
caselId	string	The unique identifier for the case.							

setUserData

Signature	<static> setUserData(<i>interactionId</i> , <i>keyValues</i>)											
Description	Sets the user data on the live interaction (for voice, this means the interaction is not in the IDLE state). This request overwrites any existing keys on the user data. The service-client-api.user-data.write-allowed option might restrict the allowed key/value pairs.											
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique identifier for the interaction.</td> </tr> <tr> <td>keyValues</td> <td>object</td> <td>The key value pairs to set on the user data.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique identifier for the interaction.	keyValues	object	The key value pairs to set on the user data.		
Name	Type	Description										
interactionId	string	The unique identifier for the interaction.										
keyValues	object	The key value pairs to set on the user data.										

markdone

Signature	<static> markdone(<i>interactionId</i>)								
Description	Mark done the selected interaction.								
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique identifier for the interaction.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique identifier for the interaction.		
Name	Type	Description							
interactionId	string	The unique identifier for the interaction.							

blockMarkdone

Signature	<static> blockMarkdone(<i>interactionId</i> , <i>warningMessage</i>)											
Description	Block the mark done operation on the selected interaction. The "markdone" event must be subscribed to receive the event which informs that there is a delay in blocking the markdone operation with this method.											
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique interaction identifier of the interaction to prevent the mark done operation.</td> </tr> <tr> <td>warningMessage</td> <td>string</td> <td>The warning message.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique interaction identifier of the interaction to prevent the mark done operation.	warningMessage	string	The warning message.		
Name	Type	Description										
interactionId	string	The unique interaction identifier of the interaction to prevent the mark done operation.										
warningMessage	string	The warning message.										

unlockMarkdone

Signature	<static> unlockMarkdone(<i>interactionId</i>)								
Description	Unblock the mark done operation on the selected interaction that was previously blocked.								
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique interaction identifier of the interaction to prevent the mark done operation.</td> </tr> </tbody> </table>	Name	Type	Description	interactionId	string	The unique interaction identifier of the interaction to prevent the mark done operation.		
Name	Type	Description							
interactionId	string	The unique interaction identifier of the interaction to prevent the mark done operation.							

Type Definitions

The Interaction namespace includes the following object types:

- [Interaction](#)
- [Party](#)

Interaction

Description	Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.																				
Type	Object																				
Properties	<table border="1"> <thead> <tr> <th style="text-align: center;">Name</th> <th style="text-align: center;">Type</th> <th style="text-align: center;">Description</th> </tr> </thead> <tbody> <tr> <td>interactionId</td> <td>string</td> <td>The unique identifier for the interaction. Note: This is a client-side ID that is lost on the next session or refresh.</td> </tr> <tr> <td>parentInteractionId</td> <td>string</td> <td>The unique identifier for the parent interaction. Note: This is a client-side ID that is lost on the next session or refresh.</td> </tr> <tr> <td>caseId</td> <td>string</td> <td>This identifier targets the case that this interaction is part of.</td> </tr> <tr> <td>userData</td> <td>object</td> <td>The attached user data key/value object that is updated with each interaction event.</td> </tr> <tr> <td>state</td> <td>string</td> <td>The current state of the interaction. Possible values are: <ul style="list-style-type: none"> • UNKNOWN — An unknown state. </td> </tr> </tbody> </table>			Name	Type	Description	interactionId	string	The unique identifier for the interaction. Note: This is a client-side ID that is lost on the next session or refresh.	parentInteractionId	string	The unique identifier for the parent interaction. Note: This is a client-side ID that is lost on the next session or refresh.	caseId	string	This identifier targets the case that this interaction is part of.	userData	object	The attached user data key/value object that is updated with each interaction event.	state	string	The current state of the interaction. Possible values are: <ul style="list-style-type: none"> • UNKNOWN — An unknown state.
Name	Type	Description																			
interactionId	string	The unique identifier for the interaction. Note: This is a client-side ID that is lost on the next session or refresh.																			
parentInteractionId	string	The unique identifier for the parent interaction. Note: This is a client-side ID that is lost on the next session or refresh.																			
caseId	string	This identifier targets the case that this interaction is part of.																			
userData	object	The attached user data key/value object that is updated with each interaction event.																			
state	string	The current state of the interaction. Possible values are: <ul style="list-style-type: none"> • UNKNOWN — An unknown state. 																			

<p>Description</p>	<p>Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.</p>		
	<p>Name</p>	<p>Type</p>	<p>Description</p>
			<ul style="list-style-type: none"> • IDLE — Specifies a non-active interaction which could be closed. • RINGING — The inbound call is ringing. • DIALING — The outbound call is ringing. • TALKING — The call is established. • HELD — The call is on hold. • PREVIEW — The interaction is a call preview. • INVITED — The open media interaction is inviting. • ACCEPTED — The open media interaction is accepted. • CREATED — The open

<p>Description</p>	<p>Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.</p>								
	<table border="1"> <thead> <tr> <th data-bbox="824 384 1032 426">Name</th> <th data-bbox="1032 384 1240 426">Type</th> <th data-bbox="1240 384 1445 426">Description</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td data-bbox="1240 426 1445 1820"> <p>media interaction has been created.</p> <ul style="list-style-type: none"> • PULLED — The open media interaction has been pulled from a workbin. • REVOKED — The open media interaction has been revoked. • COMPLETED — The open media interaction has been completed (Mark as done). • ERROR — The open media interaction has an error. • SAVED — The open media interaction has been saved. • TRANSFERRING — The open media </td> </tr> </tbody> </table>			Name	Type	Description			<p>media interaction has been created.</p> <ul style="list-style-type: none"> • PULLED — The open media interaction has been pulled from a workbin. • REVOKED — The open media interaction has been revoked. • COMPLETED — The open media interaction has been completed (Mark as done). • ERROR — The open media interaction has an error. • SAVED — The open media interaction has been saved. • TRANSFERRING — The open media
Name	Type	Description							
		<p>media interaction has been created.</p> <ul style="list-style-type: none"> • PULLED — The open media interaction has been pulled from a workbin. • REVOKED — The open media interaction has been revoked. • COMPLETED — The open media interaction has been completed (Mark as done). • ERROR — The open media interaction has an error. • SAVED — The open media interaction has been saved. • TRANSFERRING — The open media 							

<p>Description</p>	<p>Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.</p>																										
	<table border="1"> <thead> <tr> <th data-bbox="824 384 1032 426">Name</th> <th data-bbox="1032 384 1240 426">Type</th> <th data-bbox="1240 384 1445 426">Description</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td data-bbox="1240 426 1445 552"> <p>interaction is being transferred.</p> </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 552 1445 867"> <ul style="list-style-type: none"> • TRANSFER_COMPLETED — The open media interaction has been transferred and the transfer has been completed. </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 867 1445 1119"> <ul style="list-style-type: none"> • INVITED_CONFERENCE — The open media interaction receives a conference invitation. </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 1119 1445 1350"> <ul style="list-style-type: none"> • LEFT_CONFERENCE — The open media interaction has left the conference. </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 1350 1445 1539"> <ul style="list-style-type: none"> • USER_DATA_ATTACHED — Data has been attached to the interaction. </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 1539 1445 1749"> <ul style="list-style-type: none"> • USER_DATA_UPDATED — The attached data has changed in the interaction. </td> </tr> <tr> <td></td> <td></td> <td data-bbox="1240 1749 1445 1822"> <ul style="list-style-type: none"> • JOIN_PENDING </td> </tr> </tbody> </table>			Name	Type	Description			<p>interaction is being transferred.</p>			<ul style="list-style-type: none"> • TRANSFER_COMPLETED — The open media interaction has been transferred and the transfer has been completed. 			<ul style="list-style-type: none"> • INVITED_CONFERENCE — The open media interaction receives a conference invitation. 			<ul style="list-style-type: none"> • LEFT_CONFERENCE — The open media interaction has left the conference. 			<ul style="list-style-type: none"> • USER_DATA_ATTACHED — Data has been attached to the interaction. 			<ul style="list-style-type: none"> • USER_DATA_UPDATED — The attached data has changed in the interaction. 			<ul style="list-style-type: none"> • JOIN_PENDING
Name	Type	Description																									
		<p>interaction is being transferred.</p>																									
		<ul style="list-style-type: none"> • TRANSFER_COMPLETED — The open media interaction has been transferred and the transfer has been completed. 																									
		<ul style="list-style-type: none"> • INVITED_CONFERENCE — The open media interaction receives a conference invitation. 																									
		<ul style="list-style-type: none"> • LEFT_CONFERENCE — The open media interaction has left the conference. 																									
		<ul style="list-style-type: none"> • USER_DATA_ATTACHED — Data has been attached to the interaction. 																									
		<ul style="list-style-type: none"> • USER_DATA_UPDATED — The attached data has changed in the interaction. 																									
		<ul style="list-style-type: none"> • JOIN_PENDING 																									

Description	Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.								
	<table border="1"> <thead> <tr> <th data-bbox="820 378 1031 426">Name</th> <th data-bbox="1034 378 1237 426">Type</th> <th data-bbox="1240 378 1445 426">Description</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td data-bbox="1240 430 1445 1831"> <ul style="list-style-type: none"> — Trying to join the chat session. • JOIN_FAILED — The connection with the chat server failed. • HISTORY_IN_PROGRESS — Loading the content of the chat interaction. • HISTORY_DONE — The content of the chat interaction has been loaded. • CANCELLED — The outbound email is cancelled. • SENT — The outbound email is sent. • READY — The call preview is ready. • CANCELED — The call preview is cancelled. • REJECTED </td> </tr> </tbody> </table>			Name	Type	Description			<ul style="list-style-type: none"> — Trying to join the chat session. • JOIN_FAILED — The connection with the chat server failed. • HISTORY_IN_PROGRESS — Loading the content of the chat interaction. • HISTORY_DONE — The content of the chat interaction has been loaded. • CANCELLED — The outbound email is cancelled. • SENT — The outbound email is sent. • READY — The call preview is ready. • CANCELED — The call preview is cancelled. • REJECTED
Name	Type	Description							
		<ul style="list-style-type: none"> — Trying to join the chat session. • JOIN_FAILED — The connection with the chat server failed. • HISTORY_IN_PROGRESS — Loading the content of the chat interaction. • HISTORY_DONE — The content of the chat interaction has been loaded. • CANCELLED — The outbound email is cancelled. • SENT — The outbound email is sent. • READY — The call preview is ready. • CANCELED — The call preview is cancelled. • REJECTED 							

Description	Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.																										
	<table border="1"> <thead> <tr> <th data-bbox="824 384 1031 426">Name</th> <th data-bbox="1036 384 1235 426">Type</th> <th data-bbox="1240 384 1437 426">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="824 432 1031 573"></td> <td data-bbox="1036 432 1235 573"></td> <td data-bbox="1240 432 1437 573"> — The call preview is rejected. </td> </tr> <tr> <td data-bbox="824 579 1031 667">previousState</td> <td data-bbox="1036 579 1235 667">string</td> <td data-bbox="1240 579 1437 667"> The previous state of the interaction. </td> </tr> <tr> <td data-bbox="824 674 1031 825">parties</td> <td data-bbox="1036 674 1235 825">Array.<interactionParty></td> <td data-bbox="1240 674 1437 825"> A collection of all the parties involved in the interaction. </td> </tr> <tr> <td data-bbox="824 831 1031 1031">isConsultation</td> <td data-bbox="1036 831 1235 1031">boolean</td> <td data-bbox="1240 831 1437 1031"> This property is true if the interaction is a consultation; otherwise, it's false. </td> </tr> <tr> <td data-bbox="824 1037 1031 1598">isMainCaseInteraction</td> <td data-bbox="1036 1037 1235 1598">boolean</td> <td data-bbox="1240 1037 1437 1598"> This property is true if the interaction is the main interaction in the customer case; otherwise, it's false. In Workspace Web Edition, the main interaction is related to Case Information, Disposition, Note, Contact Profile, and so on. </td> </tr> <tr> <td data-bbox="824 1604 1031 1755">callUuid</td> <td data-bbox="1036 1604 1235 1755">string</td> <td data-bbox="1240 1604 1437 1755"> The UUID of the call. This attribute is only on voice interactions. </td> </tr> <tr> <td data-bbox="824 1761 1031 1818">direction</td> <td data-bbox="1036 1761 1235 1818">string</td> <td data-bbox="1240 1761 1437 1818"> The call direction. </td> </tr> </tbody> </table>			Name	Type	Description			— The call preview is rejected.	previousState	string	The previous state of the interaction.	parties	Array.<interactionParty>	A collection of all the parties involved in the interaction.	isConsultation	boolean	This property is true if the interaction is a consultation; otherwise, it's false.	isMainCaseInteraction	boolean	This property is true if the interaction is the main interaction in the customer case; otherwise, it's false. In Workspace Web Edition, the main interaction is related to Case Information, Disposition, Note, Contact Profile, and so on.	callUuid	string	The UUID of the call. This attribute is only on voice interactions.	direction	string	The call direction.
Name	Type	Description																									
		— The call preview is rejected.																									
previousState	string	The previous state of the interaction.																									
parties	Array.<interactionParty>	A collection of all the parties involved in the interaction.																									
isConsultation	boolean	This property is true if the interaction is a consultation; otherwise, it's false.																									
isMainCaseInteraction	boolean	This property is true if the interaction is the main interaction in the customer case; otherwise, it's false. In Workspace Web Edition, the main interaction is related to Case Information, Disposition, Note, Contact Profile, and so on.																									
callUuid	string	The UUID of the call. This attribute is only on voice interactions.																									
direction	string	The call direction.																									

Description	Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.																							
	<table border="1"> <thead> <tr> <th data-bbox="829 384 1032 426">Name</th> <th data-bbox="1032 384 1235 426">Type</th> <th data-bbox="1235 384 1448 426">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="829 426 1032 663"></td> <td data-bbox="1032 426 1235 663"></td> <td data-bbox="1235 426 1448 663">Possible values are: IN, OUT or UNKNOWN. This attribute is only on voice interactions.</td> </tr> <tr> <td data-bbox="829 663 1032 1010">callType</td> <td data-bbox="1032 663 1235 1010">string</td> <td data-bbox="1235 663 1448 1010">The call type. Possible values are: INTERNAL, INBOUND, OUTBOUND, CONSULT or UNKNOWN. This attribute is only on voice interactions.</td> </tr> <tr> <td data-bbox="829 1010 1032 1220">ani</td> <td data-bbox="1032 1010 1235 1220">string</td> <td data-bbox="1235 1010 1448 1220">The Automatic Number Identification service. This attribute is only on voice interactions.</td> </tr> <tr> <td data-bbox="829 1220 1032 1430">dnis</td> <td data-bbox="1032 1220 1235 1430">string</td> <td data-bbox="1235 1220 1448 1430">The Dialed Number Identification Service. This attribute is only on voice interactions.</td> </tr> <tr> <td data-bbox="829 1430 1032 1745">recordingState</td> <td data-bbox="1032 1430 1235 1745">string</td> <td data-bbox="1235 1430 1448 1745">The call recording state. Possible values are: STOPPED, RECORDING or PAUSED. This attribute is only on voice interactions.</td> </tr> <tr> <td data-bbox="829 1745 1032 1816">isCaseSelected</td> <td data-bbox="1032 1745 1235 1816">boolean</td> <td data-bbox="1235 1745 1448 1816">Is true if the case</td> </tr> </tbody> </table>			Name	Type	Description			Possible values are: IN, OUT or UNKNOWN. This attribute is only on voice interactions.	callType	string	The call type. Possible values are: INTERNAL, INBOUND, OUTBOUND, CONSULT or UNKNOWN. This attribute is only on voice interactions.	ani	string	The Automatic Number Identification service. This attribute is only on voice interactions.	dnis	string	The Dialed Number Identification Service. This attribute is only on voice interactions.	recordingState	string	The call recording state. Possible values are: STOPPED, RECORDING or PAUSED. This attribute is only on voice interactions.	isCaseSelected	boolean	Is true if the case
Name	Type	Description																						
		Possible values are: IN, OUT or UNKNOWN. This attribute is only on voice interactions.																						
callType	string	The call type. Possible values are: INTERNAL, INBOUND, OUTBOUND, CONSULT or UNKNOWN. This attribute is only on voice interactions.																						
ani	string	The Automatic Number Identification service. This attribute is only on voice interactions.																						
dnis	string	The Dialed Number Identification Service. This attribute is only on voice interactions.																						
recordingState	string	The call recording state. Possible values are: STOPPED, RECORDING or PAUSED. This attribute is only on voice interactions.																						
isCaseSelected	boolean	Is true if the case																						

<p>Description</p>	<p>Represents the JSON structure of an interaction. Attributes specific to voice interactions are: callUuid, direction, callType, ani, dnis and recordingState.</p>														
	<table border="1"> <thead> <tr> <th data-bbox="824 384 1032 426">Name</th> <th data-bbox="1032 384 1239 426">Type</th> <th data-bbox="1239 384 1453 426">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="824 426 1032 573"></td> <td data-bbox="1032 426 1239 573"></td> <td data-bbox="1239 426 1453 573"> containing this interaction is selected, otherwise is false. </td> </tr> <tr> <td data-bbox="824 573 1032 783">isCaseExpanded</td> <td data-bbox="1032 573 1239 783">boolean</td> <td data-bbox="1239 573 1453 783"> Is true if the case containing this interaction is expanded, otherwise is false. </td> </tr> <tr> <td data-bbox="824 783 1032 1024">interactionUUID</td> <td data-bbox="1032 783 1239 1024">string</td> <td data-bbox="1239 783 1453 1024"> The attr_itx_id for a multimedia interaction or the callUuid for a voice interaction. </td> </tr> </tbody> </table>			Name	Type	Description			containing this interaction is selected, otherwise is false.	isCaseExpanded	boolean	Is true if the case containing this interaction is expanded, otherwise is false.	interactionUUID	string	The attr_itx_id for a multimedia interaction or the callUuid for a voice interaction.
Name	Type	Description													
		containing this interaction is selected, otherwise is false.													
isCaseExpanded	boolean	Is true if the case containing this interaction is expanded, otherwise is false.													
interactionUUID	string	The attr_itx_id for a multimedia interaction or the callUuid for a voice interaction.													

Party

<p>Description</p>	<p>Represents the JSON structure of a party.</p>								
<p>Type</p>	<p>Object</p>								
<p>Properties</p>	<table border="1"> <thead> <tr> <th data-bbox="824 1262 1032 1304">Name</th> <th data-bbox="1032 1262 1239 1304">Type</th> <th data-bbox="1239 1262 1453 1304">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="824 1304 1032 1373">name</td> <td data-bbox="1032 1304 1239 1373">string</td> <td data-bbox="1239 1304 1453 1373"> The name of the party. </td> </tr> </tbody> </table>			Name	Type	Description	name	string	The name of the party.
Name	Type	Description							
name	string	The name of the party.							