



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Web Edition Developer's Guide and API Reference

System Namespace

System Namespace

Contents

- [1 System Namespace](#)
 - [1.1 Methods](#)

Methods

The System namespace includes the following methods:

- [getAllowedServices](#)
- [triggerActivity](#)
- [closeToast](#)
- [popupToast](#)
- [updateToast](#)

getAllowedServices

Signature	<static> getAllowedServices() → {Array.<string>}
Description	Gets the list of allowed services, as determined by the Security Configuration . If the domain of the web application that calls this method isn't listed in the service-client-api.accepted-web-content-origins option, then this method fails.
Returns	Array.<string>

triggerActivity

Signature	<static> triggerActivity()
Description	Triggers a fake activity to prevent the inactivity timer from closing the agent session.

popupToast

Signature	<static> popupToast(parameters) → {string}												
Description	Pops up a new custom toast.												
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>title</td> <td>string</td> <td>The title</td> </tr> <tr> <td>iconUrl</td> <td>string</td> <td>The URL of the icon you want to display in the title bar of the custom toast popup.</td> </tr> <tr> <td>subject</td> <td>string</td> <td>Optional. The subject</td> </tr> </tbody> </table>	Name	Type	Description	title	string	The title	iconUrl	string	The URL of the icon you want to display in the title bar of the custom toast popup.	subject	string	Optional. The subject
Name	Type	Description											
title	string	The title											
iconUrl	string	The URL of the icon you want to display in the title bar of the custom toast popup.											
subject	string	Optional. The subject											

Signature	<static> popupToast(parameters) → {string}		
	Name	Type	Description
	message	string	Optional. The message
	keyValues	string	Optional. JSON object used to fill the key value pair list. For example: {"key1" ; "value one", "key2" ; "value two", "key3" ; "value three"}.
	buttons	Array.<string>	Optional. Each character string in this array becomes a button.
	buttonShowDismiss	boolean	Optional. If set to true, displays the Show and Dismiss buttons and pops up the current iframe if the Show button is pushed. If set to false, displays "OK" or custom buttons based on the parameter's buttons.
	autoCloseTime	number	Optional. If set to greater than 0, the popup is automatically closed after the specified milliseconds.
	sendToMyMessage	boolean	Optional. If set to true, sends the subject , iconUrl , title ,

Signature	<static> popupToast(parameters) → {string}						
	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>keyValues, and message parameters to the MyMessage panel.</td> </tr> </tbody> </table>	Name	Type	Description			keyValues , and message parameters to the MyMessage panel.
Name	Type	Description					
		keyValues , and message parameters to the MyMessage panel.					
Returns	A unique identifier						

updateToast

Signature	<static> updateToast(id, parameters) → {boolean}																								
Description	Updates the specified toast.																								
Parameters	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>id</td> <td>string</td> <td>The identifier of the toast to update. The identifier is returned by the popupToast method.</td> </tr> <tr> <td></td> <td></td> <td> <table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>title</td> <td>string</td> <td>The title</td> </tr> <tr> <td>iconURL</td> <td>string</td> <td>The URL of the icon you want to display in the title bar of the custom toast popup.</td> </tr> <tr> <td>subject</td> <td>string</td> <td>Optional. The</td> </tr> </tbody> </table> </td> </tr> <tr> <td>parameters</td> <td>object</td> <td></td> </tr> </tbody> </table>	Name	Type	Description	id	string	The identifier of the toast to update. The identifier is returned by the popupToast method.			<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>title</td> <td>string</td> <td>The title</td> </tr> <tr> <td>iconURL</td> <td>string</td> <td>The URL of the icon you want to display in the title bar of the custom toast popup.</td> </tr> <tr> <td>subject</td> <td>string</td> <td>Optional. The</td> </tr> </tbody> </table>	Name	Type	Description	title	string	The title	iconURL	string	The URL of the icon you want to display in the title bar of the custom toast popup.	subject	string	Optional. The	parameters	object	
Name	Type	Description																							
id	string	The identifier of the toast to update. The identifier is returned by the popupToast method.																							
		<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>title</td> <td>string</td> <td>The title</td> </tr> <tr> <td>iconURL</td> <td>string</td> <td>The URL of the icon you want to display in the title bar of the custom toast popup.</td> </tr> <tr> <td>subject</td> <td>string</td> <td>Optional. The</td> </tr> </tbody> </table>	Name	Type	Description	title	string	The title	iconURL	string	The URL of the icon you want to display in the title bar of the custom toast popup.	subject	string	Optional. The											
Name	Type	Description																							
title	string	The title																							
iconURL	string	The URL of the icon you want to display in the title bar of the custom toast popup.																							
subject	string	Optional. The																							
parameters	object																								

Signature	<static> updateToast(id, parameters) → {boolean}																				
	Name	Type	Description																		
			<table border="1"> <thead> <tr> <th data-bbox="1256 365 1312 407">Name</th> <th data-bbox="1312 365 1367 407">Type</th> <th data-bbox="1367 365 1463 407">Description</th> </tr> </thead> <tbody> <tr> <td data-bbox="1256 407 1312 449"></td> <td data-bbox="1312 407 1367 449"></td> <td data-bbox="1367 407 1463 449">subject.</td> </tr> <tr> <td data-bbox="1256 449 1312 533">message</td> <td data-bbox="1312 449 1367 533">string</td> <td data-bbox="1367 449 1463 533">Optional. The subject.</td> </tr> <tr> <td data-bbox="1256 533 1312 1100">keyValues</td> <td data-bbox="1312 533 1367 1100">Object</td> <td data-bbox="1367 533 1463 1100">Optional. JSON object used to fill the key value pair list. For example: {"key1" : "value one", "key2" : "value two", "key3" : "value three"}.</td> </tr> <tr> <td data-bbox="1256 1100 1312 1373">buttonArray</td> <td data-bbox="1312 1100 1367 1373">Array<string></td> <td data-bbox="1367 1100 1463 1373">Each character string in this array becomes a button.</td> </tr> <tr> <td data-bbox="1256 1373 1312 1814">buttonDismiss</td> <td data-bbox="1312 1373 1367 1814">boolean</td> <td data-bbox="1367 1373 1463 1814">If set to true, displays Show and Dismiss buttons and pops up the current iframe</td> </tr> </tbody> </table>	Name	Type	Description			subject.	message	string	Optional. The subject.	keyValues	Object	Optional. JSON object used to fill the key value pair list. For example: {"key1" : "value one", "key2" : "value two", "key3" : "value three"}.	buttonArray	Array<string>	Each character string in this array becomes a button.	buttonDismiss	boolean	If set to true, displays Show and Dismiss buttons and pops up the current iframe
Name	Type	Description																			
		subject.																			
message	string	Optional. The subject.																			
keyValues	Object	Optional. JSON object used to fill the key value pair list. For example: {"key1" : "value one", "key2" : "value two", "key3" : "value three"}.																			
buttonArray	Array<string>	Each character string in this array becomes a button.																			
buttonDismiss	boolean	If set to true, displays Show and Dismiss buttons and pops up the current iframe																			

Signature	<static> updateToast(id, parameters) → {boolean}								
	Name	Type	Description						
			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #f2f2f2;">Name</th> <th style="background-color: #f2f2f2;">Type</th> <th style="background-color: #f2f2f2;">Description</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>if the Show button is pushed. If set to false, displays "OK" or custom buttons based on the parameter's buttons.</td> </tr> </tbody> </table>	Name	Type	Description			if the Show button is pushed. If set to false, displays "OK" or custom buttons based on the parameter's buttons.
Name	Type	Description							
		if the Show button is pushed. If set to false, displays "OK" or custom buttons based on the parameter's buttons.							
Returns	true if the toast has been updated; false if the toast identifier has not been found.								

closeToast

Signature	<static> closeToast(id) → {boolean}		
Description	Closes the specified toast.		
Parameters	Name	Type	Description
	id	string	The identifier of the toast to close. The identifier is returned by the <code>popupToast</code> method.
Returns	true if the toast has been updated; false if the toast identifier has not been found.		