



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

Create

Create

This operation is part of the [Twitter API](#) section of the [Web Services API](#).

Overview

Creates a new empty Twitter interaction.

Request URL	/api/v2/me/tweets
HTTP Method	POST
Required Features	api-multimedia

Parameters

Parameter	Value
operationName	Create
queuePath	The URI of the queue where Web Services should place this Twitter interaction.
userData	The key value data to attach. (optional)

Samples

Request

```
POST /api/v2/me/tweets
{
  "operationName": "Create",
  "queuePath": "/queues/995655ec-81a5-46b0-82d0-3f2c5eca263d"
}
```

HTTP Response

```
{
  "statusCode": 0,
  "referenceId": 10,
}
```

CometD Response

```
{
  "messageType": "TwitterStateChangeMessage",
  "notificationType": "StatusChange",
  "referenceId": 10,
  "twitter": {
    "capabilities": [
      "Cancel",
      "Send",
      "AddComment",
      "AttachUserData",
      "UpdateUserData",
      "DeleteUserData",
      "SetDisposition",
      "SetInFocus",
      "Transfer"
    ],
    "id": "01QQQG2MU214P05G",
    "state": "Composing",
    "twitterType": "Outbound",
    "uri": "http://192.168.83.25:8080/api/v2/tweet/01QQQG2MU214P05G"
  }
}
```

Field	Description
messageType	The category of message.
notificationType	The purpose of the notification.
twitter	The element containing all Twitter-specific data.