



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

[Unfollow](#)

5/4/2025

Unfollow

This operation is part of the [Twitter API](#) section of the [Web Services API](#).

Overview

Disables monitoring of a specific Twitter user's tweets.

Request URL	/api/v2/me/tweets
HTTP Method	POST
Required Features	api-multimedia

Parameters

Parameter	Value
operationName	Unfollow
twitterUserId	A Twitter user's numeric unique identifier.
from	Twitter account name on whose behalf the Unfollow operation is performed.

Samples

Request

```
POST api/v2/me/tweets
{
  "operationName": "Unfollow",
  "twitterUserId": "1234567890",
  "from": "customer_support"
}
```

HTTP Response

```
{
  "statusCode": 0,
  "referenceId": 1
}
```

CometD Response

Success

```
{
  "messageType": "TwitterOperationResponse",
  "referenceId": 1,
  "success": "true"
}
```

Failure

```
{
  "messageType": "TwitterOperationResponse",
  "referenceId": 1,
  "success": "false",
  "errorMessage": "Unable to perform twitter operation"
}
```