



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Services API Reference

Create Settings Group

# Create Settings Group

This operation is part of the [User Settings API](#) section of the [Web Services API](#).

## Overview

Creates a new settings group for the specified user.

|                          |   |
|--------------------------|---|
| <b>Request URL</b>       | /users/{user id}/settings<br>or<br>/me/settings |
| <b>HTTP Method</b>       | POST  |
| <b>Required Features</b> | api-provisioning-write                          |

## Parameters

| Parameter   | Value  |
|-------------|--|
| displayName | A user-friendly name describing the settings group.  |
| name        | A URI-compatible name for the settings group. This name is used as part of the URI to access the group. For example, GET /settings/my-settings-group.  |
| key         | Specifies an attribute that Web Services uses to identify the settings in this group if they are modified. The value of the "key" attribute must be unique for every setting and is read-only after the setting is created. This parameter is mandatory. |

## Samples

### Request

```
POST /api/v2/me/settings
{
  "displayName": "My Setting Group",
  "name": "my-setting-group",
  "key": "name" //specifies that each setting in this group must have a "name" attribute
                with a unique value
}
```

## HTTP Response

```
{  
  "statusCode": 0  
}
```