



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services and Applications Configuration Guide

Accessibility

Accessibility

Workspace Web Edition provides the following options for managing accessibility features:

Contents

- **1 Accessibility**
 - 1.1 accessibility.agent-state-change-bell
 - 1.2 accessibility.dialog-bell
 - 1.3 accessibility.dialog-error-bell
 - 1.4 accessibility.focus-on-interaction-toast
 - 1.5 accessibility.interaction-state-change-bell
 - 1.6 accessibility.<media-type>.focus-on-interaction-toast
 - 1.7 accessibility.outbound-campaign-state-change-bell
 - 1.8 accessibility.visual-impairment-profile
 - 1.9 accessibility.voicemail-message-change-bell
 - 1.10 accessibility.voicemail-new-message-change-bell
 - 1.11 accessibility.warning-message-bell
 - 1.12 keyboard.shortcut.interaction.next
 - 1.13 keyboard.shortcut.interaction.previous
 - 1.14 keyboard.shortcut.jump-to-last-error

accessibility.agent-state-change-bell

- Default Value:
- Valid Values: All special characters that are valid in a URL file path, the '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the agent state change sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the pipe '|' character. The first is the sound file name (the BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to a MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:
 - -1 — play and repeat the sound until an explicit message, such as event established, causes it to stop.
 - 0 — play the whole sound once
 - an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

accessibility.dialog-bell

- Default value:
- Valid value: All special characters that are valid URL file path, '|' separator and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the dialog sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the character '|'. The first is the sound file name (BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to a MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:
 - 0 — play the whole sound once
 - an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

accessibility.dialog-error-bell

- Default value:
- Valid value: All special characters that are valid URL file path, '|' separator and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the error alert sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the character '|'. The first is the sound file name (BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to a MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:
 - 0 — play the whole sound once
 - an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

accessibility.focus-on-interaction-toast

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the session is started or restarted.
- Description: Specifies whether the **Interaction Notification** views receive the focus when they are displayed. This option does not rely on the **accessibility.visual-impairment-profile** option; therefore, it applies to all configured agents, not just visually impaired agents.

accessibility.interaction-state-change-bell

- Default Value:
- Valid Values: All special characters that are valid in a URL file path, the '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the interaction state change sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the pipe ('|') character. The first is the sound file name (the BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to a MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:
 - -1 — play and repeat the sound until an explicit message, such as event established, causes it to stop.
 - 0 — play the whole sound once
 - an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

accessibility.<media-type>.focus-on-interaction-toast

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the session is started or restarted.
- Description: Specifies whether the **Interaction Notification** views associated with the specified media type receive the focus when they are displayed. This option does not rely on the **accessibility.visual-impairment-profile** option; therefore, it applies to all configured agents, not just visually impaired agents.

accessibility.outbound-campaign-state-change-bell

- Default Value:
- Valid Values: All special characters that are valid in a URL file path, the '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the outbound campaign state change sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the pipe ('|') character. The first is

the sound file name (the BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to an MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:

- 0 — play the whole sound once
- an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

accessibility.visual-impairment-profile

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the session is started or restarted.
- Description: Specifies whether the profile for visually impaired users is active. This option enables users to navigate interface elements from keyboard navigation and tooltips by using a Screen Reader application. Some components might change their behavior in this mode. For example, Team Communicator is collapsed in this configuration.

accessibility.voicemail-message-change-bell

- Default Value:
- Valid Values: All special characters that are in valid URL file path, '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the Voice Mail counter change sound-configuration string for new or old messages. For example: 'BELL|7|0'. The value has three components that are separated by the pipe character '|'.
 - Sound file name (BELL, RING, CHORD or WARNING, predefined aliases, or an absolute URL to a mp3 file).
 - Priority level. The higher the integer, the higher the priority.
 - Duration. 0 means to play the whole sound one time. An integer greater than 0 means a time in milliseconds to play and repeat the sound.

accessibility.voicemail-new-message-change-bell

- Default Value:
- Valid Values: All special characters that are valid URL file path, '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the Voice Mail counter change sound-configuration string for new messages. For example: 'BELL|7|0'. The value has three components that are separated by the pipe character '|'.
 - Sound file name (BELL, RING, CHORD or WARNING, predefined aliases, or an absolute URL to a mp3 file).
 - Priority level. The higher the integer, the higher the priority.
 - Duration. 0 means to play the whole sound one time. An integer greater than 0 means a time in milliseconds to play and repeat the sound.

accessibility.warning-message-bell

- Default Value:
- Valid Values: All special characters that are valid in a URL file path, the '|' separator, and numeric values.
- Changes take effect: When the session is started or restarted.
- Description: Specifies the warning message sound-configuration string. For example: 'BELL|7|0'. The value has three components that are separated by the pipe '|' character. The first is the sound file name (the BELL, RING, CHORD or WARNING predefined aliases or an absolute URL to a MP3 file). The second is a priority — the higher the integer, the higher the priority. The last is the duration, which can have the following values:
 - -1 — play and repeat the sound until an explicit message, such as event established, causes it to stop.
 - 0 — play the whole sound once
 - an integer greater than 0 — the length of time, in milliseconds, to play and repeat the sound

keyboard.shortcut.interaction.next

- Default Value: Alt+N
- Valid Values: The name of a key or a key combination. A key combination begins with one of the following modifier key names: Ctrl, Shift, and Alt, and ends with a character key. Separate the modifier key name from the character key with the + character.
- Changes take effect: When the session is started or restarted.
- Description: The combination of keys that a user can use as a keyboard shortcut to jump to the next case interaction.

keyboard.shortcut.interaction.previous

- Default Value: Alt+B
- Valid Values: The name of a key or a key combination the begins with one of the following modifier key names: Ctrl, Shift, and Alt, and ends with a character key. Separate the modifier key name from the character key with the + character.
- Changes take effect: When the session is started or restarted.
- Description: The combination of keys that a user can use as a keyboard shortcut to jump to the previous case interaction.

keyboard.shortcut.jump-to-last-error

- Default Value: Alt+L
- Valid Values: The name of a key or a key combination the begins with one of the following modifier key names: Ctrl, Shift, and Alt, and ends with a character key. Separate the modifier key name from the character key with the + character.
- Changes take effect: When the session is started or restarted.

- Description: The combination of keys that a user can use as a keyboard shortcut to jump the focus to the last error.