



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Services and Applications Configuration Guide

Update on Startup

4/10/2025

---

## Contents

- 1 Update on Startup
  - 1.1 opsCredentials
  - 1.2 statistics
  - 1.3 features

# Update on Startup

Workspace Web Edition provides the following options for customizing the update that occurs when the GWS server restarts:

## Important

In previous releases, a GWS server restart automatically updated global information. Now the updates are set to false by default. If you want to configure the GWS to update all global information, use the following configuration sample:

```
updateOnStartup:  
  statistics: true  
  opsCredentials: true  
  features: true
```

## opsCredentials

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the GWS server is started or restarted.
- Description: Specifies whether to update the global ops credentials to the values specified in configuration file.

## statistics

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the GWS server is started or restarted.
- Description: Specifies whether to update statistic definitions to the values specified in corresponding configuration file. This option is taken into consideration only on StatNodes.

## features

- Default Value: false
- Valid Values: true, false
- Changes take effect: When the GWS server is started or restarted.
- Description: Specifies whether to update feature definitions to the values specified in corresponding configuration file.