



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

[Change Password](#)

5/1/2025

Change Password

Operation	Attributes	Description	Valid URIs
ChangePassword	<p>oldPassword—the user's old password, encoded using base64.</p> <p>newPassword—the user's new password, encoded using base64.</p>	Verifies that the value of "oldPassword" matches the logged in user's existing password and updates it to the value of "newPassword." Configuration Server will be responsible for applying the password rules.	<p>/me</p> <p>/users/{id} (Supervisors and Admins only)</p>

Request parameters

The following request parameters are available for the "ChangePassword" operation.

Parameter	Type	Description	Access Level
firstLogin	String	Allow the user to change his or her own password, when trying to login for the first time after the user was created the user's password was changed by an administrator. Valid values: true false Default value: false	POST

Examples

The following changes the password of a user.

Request:

```
POST api/v2/me
{
  "operationName": "ChangePassword",
  "oldPassword": "MQ==",
  "newPassword": "Mg=="
}
```

Response:

```
{
  "statusCode": 0
}
```

The following changes the password when a user logs in for the first time.

Request:

Change Password

POST api/v2/me?firstLogin=true

```
{
  "operationName": "ChangePassword",
  "oldPassword": "MQ==",
  "newPassword": "Mg=="
}
```

Response:

```
{
  "statusCode": 0,
}
```