



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Services and Applications Deployment Guide

Migration to 8.5.1

# Migration to 8.5.1

From 8.5.0

## Start of Procedure

1. Stop Jetty on all the Workspace Web Edition & Web Services nodes.
2. Update Cassandra with all `cf-schema-<version>.txt` files in the `[install CD]/data` directory.
  - a. Copy the `[install CD]/data` directory to the Cassandra node host.

### Important

You must run these scripts in order, beginning with `cf-schema-8.5.100.01.txt`.

- b. For each `cf-schema-<version>.txt` file, run the following command to update the Cassandra schema:

```
[cassandra install dir]/bin/cassandra-cli -h [cassandra host] --file cf-schema-<version>.txt
```

- `[cassandra host]` is the host name (FQDN) or IP of the Cassandra node
- For each Workspace Web Edition & Web Services node, complete the following steps:
  - a. Complete the [Deploying the Web Application](#) procedure.

### Tip

Make a backup of your configuration folder (`$JETTY_HOME/genconfig`) to use as a reference for setting configuration options.

- b. Review [Configuring Workspace Web Edition & Web Services](#) and its sub-topics and set the options required for your deployment. The following configuration options have been modified in the `$JETTY_HOME/genconfig/server-settings.yaml` file in 8.5.1:

Option	Type of Change
<code>activationTimeout</code>	The default value changed from 1000 to 12000.
<code>connectionTimeout</code>	The default value changed from 400 to 4000.
<code>cmeAuthenticationEnabled</code>	Removed

- Complete the [Starting and Testing Workspace Web Edition & Web Services](#) procedure.
-

Migration to 8.5.1

---

**End of Procedure**