



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services and Applications Configuration Guide

Customer Case

12/21/2025

Customer Case

Contents

- **1 Customer Case**
 - **1.1 Evolution and Behavior of Attached Data or Case Data**
 - **1.2 Editing Case Information**
 - **1.3 Displaying Active URLs in Case Information**
 - **1.4 Add Key-Value Pair to the Case Information**

The concept of a Customer Case enables the grouping of all the information about the active interactions of all types for a single customer in one location. The Customer Case facilities enable agents to store all information about the following actions in one location, as well as:

- Handle two voice calls simultaneously.
- Toggle between two calls.
- Transfer/conference one or all interaction(s).

Evolution and Behavior of Attached Data or Case Data

Attached data that is relevant to a call evolves and changes as a call progresses through the system in a contact center. For example, during a Transfer or Conference, information about who transferred a call and when, is attached to the case data.

Editing Case Information

You can configure Workspace Web Edition to have the ability to edit the case and interaction information that is attached to an interaction. You can specify which key-value pairs are editable by an agent by adding a new section called `interaction-workspace` to the attribute of the key-value pair in Genesys Administrator, and then defining its properties. When you define the properties of an attribute in a Business Attribute, you can also specify whether it has the property `readonly` or not. Attributes that are not `readonly` can be edited by agents.

An agent can only edit case information key-value pairs of those attributes that are displayed to the agent. The table **Editing Case Information** lists the case information business-attribute keys that can be configured to be editable. For each key-value pair attribute, add a new section named `interaction-workspace`, then define the options according to the type (Boolean, string, integer, list, float, and date) of the attribute.

Editing Case Information

Attribute type	Option	Valid Values	Default Value	Description
Boolean	display-type	bool	bool (for this type)	
	read-only	true, false	true	Specifies whether this key name can be modified
	bool.default-value			
	bool.false-value		false	Value accepted for false
	bool.true-value		true	Value accepted for true
string	display-type	string	string (for this type)	
	read-only	true, false	true	Specifies whether this key name can be modified
	string.default-			

Attribute type	Option	Valid Values	Default Value	Description
	value			
	string.max-length	0 to Max Length	255	Maximum number of characters that are accepted for this option
integer	display-type	int	int (for this type)	
	read-only	true, false	true	Specifies whether this key name can be modified
	string.default-value			
	int.min-value	integer	0	Minimum value accepted
	int.max-value	integer	9007199254740992	Maximum value accepted
	int.storage-type	in or string	string	Type storage of the value
enum	display-type	enum	enum (for this type)	
	read-only	true, false	true	Specifies whether this key name can be modified
	enum.default-value			
	enum.business-attribute	(link to business attributes)	(none)	Link to a business attribute that defines the enum value. Items in this list are sorted alphabetically.
float	display-type	float	float (for this type)	
	read-only	true, false	true	Specifies whether this key name can be modified
	float.default-value			
	float.min-value	float	0	Minimum value accepted
	float.max-value	float	1.7976931348623157e308	Maximum value accepted
date	display-type	date	date (for this type)	The date is stored in the UTC format: YYYY-MM-DDThh:mm:ssTZD (refer to http://www.w3.org/TR/NOTE-

Attribute type	Option	Valid Values	Default Value	Description
				datetime). The display is based on the local from the browser.
	read-only	true, false	true	Specifies whether this key name can be modified

Displaying Active URLs in Case Information

You can configure Interaction Workspace Web Edition to render some key-values as clickable hyperlinks in the Case Information area and also enable previewing of web pages by tooltip on the clickable hyperlinks.

Use the following configuration option to control the way that hyperlinks are displayed (whether they are active or not) and to enable the display of a tooltip that displays a preview of the web page.

- **expression.url**--The option is configured by default to display most valid URLs as clickable hyperlinks.

To control the display of hyperlinks in the Case Information area, format the attached data:

- If the attached data contains a raw URL, the hyperlink will be displayed as a raw URL (for example, `http://<your web site>`).
- If the attached data is formatted in the following way, the TITLE is displayed as a clickable hyperlink, and the target is the URL:
 - `<a href="URL" title="TITLE" />`
 - `<a href="URL">TITLE</a>`

Add Key-Value Pair to the Case Information

You can enable the ability to edit the case information to add key-value pairs that are missing from the case information. For example, the country or region contact information might be missing. If the agent obtains this information, the agent can edit the Case Information view to add the data value.

Prerequisite:

- To enable a key to be added, the key must be configured as editable (refer to **Editing Case Information**).