

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Deployment Guide

Enabling Agents To Manage Contacts

Enabling Agents To Manage Contacts

Contents

- 1 Enabling Agents To Manage Contacts
 - 1.1 Procedure: Enabling agents to manage contacts
 - 1.2 Procedure: Configuring the Interaction Workspace application and Universal Contact Server to enable custom contact attributes

Refer to Framework 8.0 Genesys Administrator Help and Genesys Security Guide for detailed information on how to use Genesys Administrator and Management Framework to configure access permissions

Procedure: Enabling agents to manage contacts

Purpose: To enable an agent to view and manage contact information.

Prerequisites

- Genesys Administrator 8.0.2 or higher, configured to show Advanced View.
- A working knowledge of Genesys Administrator 8.
- An Interaction Workspace Application object exists in the Configuration Database.
- Interaction Workspace has a connection to Universal Contact Server.
- Procedure: Creating a Role and allowing an Interaction Workspace privilege and assigning a Role to an agent or agent group
- Procedure: Provisioning Interaction Workspace for the Voice channel

Start

- 1. Allow the applicable Contact Actions privileges (see Contact Management Privileges) for the role to which the agent is assigned (refer to the Procedure: Creating a Role and allowing an Interaction Workspace privilege and assigning a Role to an agent or agent group).
- 2. Configure the Contact options in the interaction-workspace section of the Interaction Workspace Application object (refer to the Contact configuration option reference for a list of Contact options and a description of how to configure them).

End

Procedure: Configuring the Interaction Workspace application and Universal Contact Server to enable custom contact attributes

Purpose: To enable an agent to search for and manage contacts based on custom Business Attributes. Business Attributes must be configured to be searchable and sortable.

In the Universal Contact Server (UCS), each contact is defined by a set of attributes that are known as Business Attributes. Business Attributes are metadata for the contact fields in the contact database. Each Business Attribute value contains a description of one of the contact fields in the contact database.

Prerequisites

- Genesys Administrator 8.0.2 or higher, configured to show Advanced View.
- · A working knowledge of Genesys Administrator 8.
- An Interaction Workspace Application object exists in the Configuration Database.
- Interaction Workspace has a connection to UCS.

• Procedure: Enabling agents to manage contacts

Start

- 1. In Genesys Administrator, create a new Business Attribute by using the name and display name of the Custom Contact Attribute.
- 2. Configure the new Business Attribute as follows:
 - Set the is-searchable to true option to make the Business Attribute available to contact searches.
 - Set the is-sortable to true option to make the Business Attribute available in the directory view.
- 3. Add the Business Attribute to the list of searchable attributes in the Interaction Workspace contact.directory-search-attributes option.
- 4. Configure the Interaction Workspace contact.directory-displayed-columns option by using the display name of the Business Attribute to enable the Business Attribute to appear as a column heading in search results (refer to the Contact configuration option reference for a list of Contact options and a description of how to configure them).
- 5. To enable the Business Attribute to display in the record details for the contact, configure the Interaction Workspace contact.displayed-attributes option that is displayed (refer to the Contact configuration option reference for a list of Contact options and a description of how to configure them).

End