



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Developer's Guide

[E-Mails](#)

E-Mails



Purpose: To provide information about customizable commands for the e-mail interactions.
Updated in: 8.1.300.17

Learn about E-Mail Commands

The e-mail commands presented in this page are restricted to e-mail interactions. However, e-mail interactions are extended open media interactions and can be used as such in open media commands. In addition to the e-mail commands, you can use:

- [Open Media](#) to place interactions in a given queue, move them to workbins, and so on.
- [Commands for the E-Mail Media](#) to manage the creation of outbound e-mails.
- [Manage Toaster](#) which also deals with e-mail interactions.

Read [Use Customizable Commands](#) to see code snippets which demonstrate the usage of the commands.

Managing E-Mail Interactions

The commands presented in this section are specific to e-mail interactions and cover the following features (this list is not exhaustive):

- Accept or decline a given e-mail;
- Load, send, reply, and save a given e-mail;
- Pull and place in queue;
- Close or stop the interactions.

Chains of Commands to Manage E-Mail Interactions

Default Commands	Parameters
Chain InteractionEmailActionFromWorkbinDeleteById Available since: 8.1.301.xx	
<ul style="list-style-type: none">• GetInteractionState	<ul style="list-style-type: none">• CommandParameter: String<ref name="String"/>

Default Commands	Parameters
<ul style="list-style-type: none"> • CanPullInteraction 	<ul style="list-style-type: none"> • CommandParameter: Dictionary<ref name="Dictionary" />
<ul style="list-style-type: none"> • DisplayWarningPullNotPossible 	<ul style="list-style-type: none"> • canPullInteractionresult: String<ref name="String" />
<ul style="list-style-type: none"> • Confirm 	<ul style="list-style-type: none"> • ActionToConfirm: String<ref name="String" /> • ConfirmParentWindow: Window<ref name="Window" />
<ul style="list-style-type: none"> • Delete 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" /> • WorkbinId: String<ref name="String" />
Chain InteractionEmailActionFromWorkbinMarkDoneByld Available since: 8.1.301.xx	
<ul style="list-style-type: none"> • GetInteractionState 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" />
<ul style="list-style-type: none"> • CanPullInteraction 	<ul style="list-style-type: none"> • CommandParameter: Dictionary<ref name="Dictionary" />
<ul style="list-style-type: none"> • DisplayWarningPullNotPossible 	<ul style="list-style-type: none"> • canPullInteractionresult: String<ref name="String" />
<ul style="list-style-type: none"> • NoChildrenOpened 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" /> • WarningMessageTarget: String<ref name="String" /> • DoNotCheckForParentId: String<ref name="String" />
<ul style="list-style-type: none"> • Confirm 	<ul style="list-style-type: none"> • ActionToConfirm: String<ref name="String" /> • ConfirmParentWindow: Window<ref name="Window" />
<ul style="list-style-type: none"> • MarkDone 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" />

Default Commands	Parameters
	<ul style="list-style-type: none"> • WorkbinId: String<ref name="String" />
Chain InteractionEmailActionFromWorkbinPullById Available since: 8.1.301.xx	
<ul style="list-style-type: none"> • GetInteractionState 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" />
<ul style="list-style-type: none"> • CanPullInteraction 	<ul style="list-style-type: none"> • CommandParameter: Dictionary<ref name="Dictionary" />
<ul style="list-style-type: none"> • DisplayWarningPullNotPossible 	<ul style="list-style-type: none"> • canPullInteractionresult: String<ref name="String" />
<ul style="list-style-type: none"> • NoChildrenOpened 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" /> • WarningMessageTarget: String<ref name="String" /> • DoNotCheckForParentId: String<ref name="String" />
<ul style="list-style-type: none"> • NoDraftWithSameParentOpened 	<ul style="list-style-type: none"> • ParentId: String<ref name="String" />
<ul style="list-style-type: none"> • PullFromWorkbin 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" /> • WorkbinId: String<ref name="String" />
<ul style="list-style-type: none"> • MoveToWorkbinOpenedParent 	<ul style="list-style-type: none"> • ParentId: String<ref name="String" />
Chain InteractionEmailActionOnOpenedEmailById	
<ul style="list-style-type: none"> • IsNotOpened 	<ul style="list-style-type: none"> • CommandParameter: String<ref name="String" >System.String</ref> • OpenedInteractionCommand: String<ref name="String" />
Chain InteractionEmailClose	
<ul style="list-style-type: none"> • IsPossibleToClose 	<ul style="list-style-type: none"> • CommandParameter: IInteractionEmail<ref name="IInteractionEmail" >Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.E

Default Commands	Parameters
<ul style="list-style-type: none"> Close 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailDelete	
<ul style="list-style-type: none"> Confirm 	<ul style="list-style-type: none"> ActionToConfirm: String<ref name="String" /> ConfirmParentWindow: Window<ref name="Window" > System.Window.Window</ref>
<ul style="list-style-type: none"> PullParentInboundEmail 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" /> DispositionCode: IDispositionCode<ref name="IDispositionCode" > Genesyslab.Desktop.Modules.Core.Model.Interactions.IDispositionCode</ref>
<ul style="list-style-type: none"> Delete 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> CleanConnectionInformation Available since: 8.1.200.16 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" />
Chain InteractionEmailDeleteById	
<ul style="list-style-type: none"> Confirm 	<ul style="list-style-type: none"> ActionToConfirm: String<ref name="String" /> ConfirmParentWindow: Window<ref name="Window" />
<ul style="list-style-type: none"> Delete 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> WorkbinId: String<ref name="String" />
Chain InteractionEmailForward Available since: 8.1.200.16	
<ul style="list-style-type: none"> IsPossibleToForward 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" > Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.IInteractionInboundEmail</ref>
<ul style="list-style-type: none"> AddForwardData 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" />

Default Commands	Parameters
	<ul style="list-style-type: none"> Destination: String<ref name="String" />
<ul style="list-style-type: none"> SetAutoClose 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul style="list-style-type: none"> SaveAttachedData 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" /> UserData: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> RequestSaveNotepad 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="IInteraction" /> NotepadViewModel: INotepadViewModel<ref name="INotepadViewModel" />
<ul style="list-style-type: none"> PlaceInQueue 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" /> Destination: String<ref name="String" /> Reason: KeyValueCollection<ref name="KeyValueCollection" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> AddRecentCall <p>Available since: 8.1.300.17</p>	<ul style="list-style-type: none"> RecentIndex: ObjectTC<ref name="ObjectTC" />Genesyslab.Desktop.Modules.TeamCommunicator.ObjectTC</ObjectTC>
Chain InteractionEmailIsPossibleToClose	
<ul style="list-style-type: none"> IsPossibleToClose 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailLoad	
<ul style="list-style-type: none"> Load 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailMarkDoneById	
<ul style="list-style-type: none"> NoChildrenOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" />

Default Commands	Parameters
	<p data-bbox="866 318 904 346">/>></p> <ul data-bbox="833 367 1388 494" style="list-style-type: none"> <li data-bbox="833 367 1388 424">• WarningMessageTarget: String<ref name="String" /> <li data-bbox="833 439 1388 494">• DoNotCheckForParentId: String<ref name="String" /> <p data-bbox="822 515 1179 542">Available since: 8.1.301.xx</p>
<ul data-bbox="181 629 311 656" style="list-style-type: none"> <li data-bbox="181 629 311 656">• Confirm 	<ul data-bbox="833 587 1429 688" style="list-style-type: none"> <li data-bbox="833 587 1429 614">• ActionToConfirm: String<ref name="String" /> <li data-bbox="833 629 1429 688">• ConfirmParentWindow: Window<ref name="Window" />
<ul data-bbox="181 798 339 825" style="list-style-type: none"> <li data-bbox="181 798 339 825">• MarkDone 	<ul data-bbox="833 756 1449 857" style="list-style-type: none"> <li data-bbox="833 756 1449 813">• CommandParameter: String<ref name="String" /> <li data-bbox="833 827 1449 857">• WorkbinId: String<ref name="String" />
<p data-bbox="169 899 646 927">Chain InteractionEmailMoveToWorkbin</p> <ul data-bbox="181 1026 425 1056" style="list-style-type: none"> <li data-bbox="181 1026 425 1056">• IsWorkbinDefined <p data-bbox="169 1079 559 1106">Deprecated since: 8.1.300.17</p>	<ul data-bbox="833 963 1449 1142" style="list-style-type: none"> <li data-bbox="833 963 1449 992">• WorkbinId: String<ref name="String" /> <li data-bbox="833 1007 1449 1064">• WorkbinOptionName: String<ref name="String" /> <li data-bbox="833 1079 1449 1136">• CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul data-bbox="181 1279 564 1309" style="list-style-type: none"> <li data-bbox="181 1279 564 1309">• IsWorkbinDestinationDefined <p data-bbox="169 1332 527 1360">Available since: 8.1.300.17</p>	<ul data-bbox="833 1195 1449 1417" style="list-style-type: none"> <li data-bbox="833 1195 1449 1224">• WorkbinId: String<ref name="String" /> <li data-bbox="833 1239 1449 1296">• WorkbinOptionName: String<ref name="String" /> <li data-bbox="833 1311 1449 1410">• CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul data-bbox="181 1501 564 1529" style="list-style-type: none"> <li data-bbox="181 1501 564 1529">• SetAttachedDadaInformation 	<ul data-bbox="833 1480 1299 1579" style="list-style-type: none"> <li data-bbox="833 1480 1299 1537">• CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul data-bbox="181 1638 274 1666" style="list-style-type: none"> <li data-bbox="181 1638 274 1666">• Save 	<ul data-bbox="833 1617 1388 1674" style="list-style-type: none"> <li data-bbox="833 1617 1388 1666">• CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul data-bbox="181 1755 401 1782" style="list-style-type: none"> <li data-bbox="181 1755 401 1782">• MoveToWorkbin 	<ul data-bbox="833 1733 1449 1812" style="list-style-type: none"> <li data-bbox="833 1733 1449 1790">• CommandParameter: String<ref name="String" />

Default Commands	Parameters
	<ul style="list-style-type: none"> • WorkbinId: String<ref name="String" />
Chain InteractionEmailPlaceInQueue	
<ul style="list-style-type: none"> • UpdateInteractionUCS <p>Available since: 8.1.300.17</p>	<ul style="list-style-type: none"> • CommandParameter: IInteraction<ref name="IInteraction" /> • NotepadViewModel: INotepadViewModel<ref name="INotepadViewModel" />
<ul style="list-style-type: none"> • Save 	<ul style="list-style-type: none"> • CommandParameter: IIInteractionEmail<ref name="IIInteractionEmail" />
<ul style="list-style-type: none"> • SetAutoClose 	<ul style="list-style-type: none"> • CommandParameter: IIInteractionOpenMedia<ref name="IIInteractionOpenMedia" /> Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.IIInteractionOpenMedia<ref name="IIInteractionOpenMedia" />
<ul style="list-style-type: none"> • SaveAttachedData <p>Available since: 8.1.100.14</p>	<ul style="list-style-type: none"> • CommandParameter: IIInteractionOpenMedia<ref name="IIInteractionOpenMedia" /> • UserData: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> • PlaceInQueue 	<ul style="list-style-type: none"> • CommandParameter: IIInteractionOpenMedia<ref name="IIInteractionOpenMedia" /> • Destination: String<ref name="String" /> • Reasons: KeyValueCollection<ref name="KeyValueCollection" />Genesyslab.Enterprise.Commons.Collections.KeyValueCollection<ref name="KeyValueCollection" /> • Extensions: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> • AddRecentCall <p>Available since: 8.1.301.xx</p>	<ul style="list-style-type: none"> • RecentIndex: ObjectTC<ref name="ObjectTC" />
Chain InteractionEmailPrint	
Available since: 8.1.300.17	
<ul style="list-style-type: none"> • Print 	<ul style="list-style-type: none"> • CommandParameter: IIInteractionEmail<ref name="IIInteractionEmail" />
Chain InteractionEmailPullById	
Available since: 8.1.300.17	

Default Commands	Parameters
<ul style="list-style-type: none"> PullInteraction 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="IInteraction" /> IW_WebcallbackInteractionId: String<ref name="String" />
Chain InteractionEmailPullFromWorkbinById	
<ul style="list-style-type: none"> NoChildrenOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> WarningMessageTarget: String<ref name="String" /> DoNotCheckForParentId: String<ref name="String" />
	Available since: 8.1.301.xx
<ul style="list-style-type: none"> NoDraftWithSameParentOpened 	<ul style="list-style-type: none"> ParentId: String<ref name="String" />
<ul style="list-style-type: none"> PullFromWorkbin 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> WorkbinId: String<ref name="String" />
<ul style="list-style-type: none"> MoveToWorkbinOpenedParent 	<ul style="list-style-type: none"> ParentId: String<ref name="String" />
Chain InteractionEmailReply	
<ul style="list-style-type: none"> RequestSaveNotepad 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="IInteraction" /> NotepadViewModel: INotepadViewModel<ref name="INotepadViewModel" />
<ul style="list-style-type: none"> IsPossibleToCreate 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" /> Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.Email
*IsInboundEmailWorkbinDefined Deprecated since: 8.1.300.17	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> IsWorkbinDestinationDefined 	<ul style="list-style-type: none"> WorkbinId: String<ref name="String" /> WorkbinOptionName: String<ref name="String" />
Available since: 8.1.300.17	

Default Commands	Parameters
	<p></p> /> <ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul style="list-style-type: none"> AddSignatureParameters Available since: 8.1.200.16 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" />
<ul style="list-style-type: none"> AddResponseSignatureParameters Available since: 8.1.200.16 	<ul style="list-style-type: none"> SignatureOptionValue: String<ref name="String" /> ESDKInboundEmail: IInteraction<ref name="IInteraction" /> Genesyslab.Enterprise.Model.Interaction.IInteraction</ref>
<ul style="list-style-type: none"> Reply 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" /> ReplyAll: String<ref name="String" /> Available since: 8.1.200.16 UserData: KeyValueCollection<ref name="KeyValueCollection" /> Available since: 8.1.200.16 SignatureParameters: Dictionary<ref name="Dictionary" /> System.Collections.Generic.Dictionary<string, object></ref> Available since: 8.1.200.16
<ul style="list-style-type: none"> InboundEmailSearchAndMoveToWorkbin 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailReplyById	
<ul style="list-style-type: none"> IsPossibleToDelete 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" />
<ul style="list-style-type: none"> NoChildrenOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> WarningMessageTarget: String<ref name="String" />

Default Commands	Parameters
	<ul style="list-style-type: none"> DoNotCheckForParentId: String<ref name="String" /> <p>Available since: 8.1.301.xx</p>
<ul style="list-style-type: none"> IsNotOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> OpenedInteractionCommand: String<ref name="String" />
<ul style="list-style-type: none"> AddSignatureParameters Available since: 8.1.200.16 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" />
<ul style="list-style-type: none"> AddResponseSignatureParameters Available since: 8.1.200.16 	<ul style="list-style-type: none"> SignatureOptionValue: String<ref name="String" /> ESDKInboundEmail: IInteraction<ref name="IInteraction" />
<ul style="list-style-type: none"> Reply 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> WorkbinId: String<ref name="String" /> Available since: 8.1.300.17 ReplyAll: String<ref name="String" /> Available since: 8.1.200.16 UserData: KeyValueCollection<ref name="KeyValueCollection" /> SignatureParameters: Dictionary<ref name="Dictionary" /> Available since: 8.1.200.16 ESDKInboundEmail: IEmaillInteraction<ref name="IEmaillInteraction" /> Genesyslab.Enterprise.Model.IEmaillInteraction</ref> Available since: 8.1.200.16
Chain InteractionEmailResend Available since: 8.1.300.17	
<ul style="list-style-type: none"> IsPossibleToCreate 	<ul style="list-style-type: none"> CommandParameter: IInteractionInboundEmail<ref name="IInteractionInboundEmail" />
<ul style="list-style-type: none"> NoChildrenOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" />

Default Commands	Parameters
	<ul style="list-style-type: none"> WarningMessageTarget: String<ref name="String" /> DoNotCheckForParentId: String<ref name="String" />
<ul style="list-style-type: none"> IsNotOpened 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> OpenedInteractionCommand: String<ref name="String" />
<ul style="list-style-type: none"> AddSignatureParameters 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" />
<ul style="list-style-type: none"> AddResponseSignatureParameters <p>Available since: 8.1.301.xx</p>	<ul style="list-style-type: none"> SignatureOptionValue: String<ref name="String" /> ESDKInboundEmail: IInteraction<ref name="IInteraction" />
<ul style="list-style-type: none"> Create 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" /> ParentInteractionId: String<ref name="String" /> InitialEmail: IMediaOpenMedia<ref name="IMediaOpenMedia" > Genesyslab.Desktop.Modules.OpenMedia.Model.Agents.IMedia InitialEmailId: String<ref name="String" /> UserData: KeyValueCollection<ref name="KeyValueCollection" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" /> SignatureParameters: Dictionary<string, object><ref name="DictionaryStringObject">Dictionary<string, object> </ref>
Chain InteractionEmailSave	
<ul style="list-style-type: none"> Save 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailSaveNewOutbound	
Available since: 8.1.200.16	

Default Commands	Parameters
<ul style="list-style-type: none"> Save 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionEmailSend	
<ul style="list-style-type: none"> RequestSaveNotepad 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="IInteraction" >Genesyslab.Desktop.Modules.Core.Model.Interaction</ref> NotepadViewModel: INotepadViewModel<ref name="INotepadViewModel" >Genesyslab.Desktop.Modules.Windows.Interactions.INotepadView</ref>
<ul style="list-style-type: none"> IsPossibleToSend 	<ul style="list-style-type: none"> CommandParameter: IInteractionOutboundEmail<ref name="IInteractionOutboundEmail" >Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.Email</ref>
<ul style="list-style-type: none"> IsPossibleToClose 	<ul style="list-style-type: none"> CommandParameter: CommandParameter<ref name="CommandParameter" >CommandParameter</ref>
<ul style="list-style-type: none"> AddQAReviewData 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Available since: 8.1.300.17	
<ul style="list-style-type: none"> SetAttachedDadaInformation <p>Available in: 8.1.000.16; deprecated in: 8.1.100.02</p>	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul style="list-style-type: none"> Save 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> Send 	<ul style="list-style-type: none"> CommandParameter: IInteractionOutboundEmail<ref name="IInteractionOutboundEmail" /> Reasons: KeyValueCollection<ref name="KeyValueCollection" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" />
Chain InteractionEmailSendInterimReply	
<ul style="list-style-type: none"> IsPossibleToSend 	<ul style="list-style-type: none"> CommandParameter: IInteractionOutboundEmail<ref name="IInteractionOutboundEmail" />

Default Commands	Parameters
	"IInteractionOutboundEmail" />
<ul style="list-style-type: none"> • IsPossibleToClose 	<ul style="list-style-type: none"> • CommandParameter: CommandParameter<ref name="CommandParameter" />IInteractionEmail<ref name="IInteractionEmail" /> <p>Modified in: 8.1.300.17</p>
<ul style="list-style-type: none"> • AddQAReviewData Available since: 8.1.300.17 	<ul style="list-style-type: none"> • CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> • SetAttachedDadaInformation 	<ul style="list-style-type: none"> • CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul style="list-style-type: none"> • Save 	<ul style="list-style-type: none"> • CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> • PullParentInboundEmail 	<ul style="list-style-type: none"> • CommandParameter: IInteractionEmail<ref name="IInteractionEmail" /> • DispositionCode: IDispositionCode<ref name="IDispositionCode" />
<ul style="list-style-type: none"> • Send 	<ul style="list-style-type: none"> • CommandParameter: IInteractionOutboundEmail<ref name="IInteractionOutboundEmail" /> • Reasons: KeyValueCollection<ref name="KeyValueCollection" /> • Extensions: KeyValueCollection<ref name="KeyValueCollection" />
Chain InteractionEmailTransferAgent	
<ul style="list-style-type: none"> • Save 	<ul style="list-style-type: none"> • CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> • SetAutoClose 	<ul style="list-style-type: none"> • CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
<ul style="list-style-type: none"> • RequestSaveNotepad 	<ul style="list-style-type: none"> • CommandParameter: IInteraction<ref name="IInteraction" />

Default Commands	Parameters
	<ul style="list-style-type: none"> <li data-bbox="864 325 1060 354">"IInteraction" /> <li data-bbox="832 369 1403 422">• NotepadViewModel: INotepadViewModel<ref name="INotepadViewModel" />
<ul style="list-style-type: none"> <li data-bbox="179 608 375 637">• TransferAgent 	<ul style="list-style-type: none"> <li data-bbox="832 494 1272 578">• CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" /> <li data-bbox="832 593 1354 623">• Destination: String<ref name="String" /> <li data-bbox="832 637 1338 690">• Reasons: KeyValueCollection<ref name="KeyValueCollection" /> <li data-bbox="832 705 1387 768">• Extensions: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> <li data-bbox="179 832 375 861">• AddRecentCall <p data-bbox="169 876 522 906">Available since: 8.1.301.xx</p>	<ul style="list-style-type: none"> <li data-bbox="832 832 1419 884">• RecentIndex: ObjectTC<ref name="ObjectTC" />
Chain InteractionEmailWorkflow	
<ul style="list-style-type: none"> <li data-bbox="179 1043 342 1072">• PromptDone <p data-bbox="169 1087 522 1117">Available since: 8.1.300.17</p>	<ul style="list-style-type: none"> <li data-bbox="832 1001 1272 1085">• CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" /> <li data-bbox="832 1100 1387 1153">• ConfirmParentWindow: Window<ref name="Window" >System.Window.Window</ref>
<ul style="list-style-type: none"> <li data-bbox="179 1339 310 1368">• Workflow 	<ul style="list-style-type: none"> <li data-bbox="832 1212 1272 1296">• CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" /> <li data-bbox="832 1311 1338 1341">• Workflow: String<ref name="String" /> <li data-bbox="832 1355 1338 1408">• Reasons: KeyValueCollection<ref name="KeyValueCollection" /> <li data-bbox="832 1423 1387 1497">• Extensions: KeyValueCollection<ref name="KeyValueCollection" />
Chain InteractionEmailWorkflowFromInteractionESDK	
<ul style="list-style-type: none"> <li data-bbox="179 1704 375 1733">• ESDKWorkflow 	<ul style="list-style-type: none"> <li data-bbox="832 1607 1305 1712">• CommandParameter: IIOpenMedialInteraction<ref name="IIOpenMedialInteraction" > Genesyslab.Enterprise.Model.Interaction.IIOpenMedialInteraction</ref> <li data-bbox="832 1727 1338 1757">• Workflow: String<ref name="String" /> <li data-bbox="832 1771 1338 1824">• Reasons: KeyValueCollection<ref name="KeyValueCollection" />

Default Commands	Parameters
	<ul style="list-style-type: none"> Extensions: KeyValueCollection<ref name="KeyValueCollection" /> AttachedDataInformation: IDispositionCode<ref name="IDispositionCode" /> DispositionCode: KeyValueCollection<ref name="KeyValueCollection" />
Chain InteractionInboundEmailPossibleToMoveToWorkbin	
<ul style="list-style-type: none"> IsInboundEmailWorkbinDefined <p>Deprecated since: 8.1.300.17</p>	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> IsWorkbinDestinationDefined <p>Available since: 8.1.300.17</p>	<ul style="list-style-type: none"> WorkbinId: String<ref name="String" /> WorkbinOptionName: String<ref name="String" /> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
Chain InteractionInboundEmailSearchAndMoveToWorkbin	
<ul style="list-style-type: none"> InboundEmailSearchAndMoveToWorkbin 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Chain InteractionOutboundEmailPossibleToMoveToWorkbin	
<ul style="list-style-type: none"> IsOutboundEmailWorkbinDefined <p>Deprecated since: 8.1.300.17</p>	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
<ul style="list-style-type: none"> IsWorkbinDestinationDefined <p>Available since: 8.1.300.17</p>	<ul style="list-style-type: none"> WorkbinId: String<ref name="String" /> WorkbinOptionName: String<ref name="String" /> CommandParameter: IInteractionOpenMedia<ref name="IInteractionOpenMedia" />
Chain InteractionOutboundEmailSearchAndMoveToWorkbin	
<ul style="list-style-type: none"> OutboundEmailSearchAndMoveToWorkbin 	<ul style="list-style-type: none"> CommandParameter: IInteractionEmail<ref name="IInteractionEmail" />
Commands common to all interactions	

Default Commands	Parameters
Chain InteractionSetAttachedDataWithDelay	<ul style="list-style-type: none"> SetAttachedData <ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="IInteraction" /> AttachedData: KeyValueCollection<ref name="KeyValueCollection" />
Chain BundleClose	
<ul style="list-style-type: none"> GetAttachedDataInformationUCS 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" > Genesyslab.Desktop.Modules.Core.Model.Interactions.IInteraction
<ul style="list-style-type: none"> UpdateNotePadForVoice Available since: 8.1.300.17 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> ResetInteractionChatConsultation 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> IsPossibleToClose 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> CompleteDispositionCodeOnBundle 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> Close 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> StopInteractionVoiceUCS 	<ul style="list-style-type: none"> CommandParameter: IInteractionsBundle<ref name="IInteractionsBundle" />
<ul style="list-style-type: none"> GetOutboundPreviewRecord 	<ul style="list-style-type: none"> CommandParameter: ICampaign<ref name="ICampaign" > Genesyslab.Enterprise.Model.Interaction.ICampaign</ref>

<references />