



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Deployment Guide

[Webproxy Options](#)

4/2/2025

Webproxy Options

Contents

- [1 Webproxy Options](#)
 - [1.1 Webproxy](#)

Webproxy

webproxy.address

- Default Value: ""
- Valid Values: An empty address to specify the default proxy configuration of your browser. A valid proxy-server address. None or an invalid address to use no proxy address.
- Changes take effect: At the next interaction.
- Description: Specifies the web-proxy host-address that is used to download from external web sites the images that are contained in the e-mail body or to pushed chat pages.

webproxy.password

- Default Value: ""
- Valid Values: The password of the proxy credentials. Leave empty to not use any credentials.
- Changes take effect: At the next interaction.
- Description: Specifies the password to be used to access the web proxy that is used to download from external web sites the images contained in e-mail body or push to chat pages.

webproxy.username

- Default Value: ""
- Valid Values: The username of the proxy credentials. Leave empty to not use any credentials.
- Changes take effect: At the next interaction.
- Description: Specifies the username to be used to access the web proxy that is used to download from external web sites the images contained in e-mail body or pushed to chat pages.