



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Deployment Guide

Workbin Options

4/7/2025

Workbin Options

Contents

- [1 Workbin Options](#)
 - [1.1 Workbin](#)

Workbin

workbin.email.draft

- Default Value: ""
- Valid Values: The name of a valid Script object of type Interaction Workbin, that is owned by Agents.
- Changes take effect: When the application is started or restarted.
- Description: The name of a valid Script object of type Interaction Workbin, that is owned by Agents.

workbin.email.draft.displayed-columns

- Default Value: To, Subject, Submitted
- Valid Values: A comma-separated list of Interaction Server interaction properties, for example: From, Subject, Received
- Changes take effect: When the application is started or restarted.
- Description: The list of interaction fields that are displayed as columns of the workbin that stores Draft e-mail interactions.

workbin.email.in-progress

- Default Value: ""
- Valid Values: The name of a valid Script object of type Interaction Workbin, that is owned by Agents.
- Changes take effect: When the application is started or restarted.
- Description: The name of the workbin that is to be used to store inbound e-mail for later processing, after an agent explicitly saved the e-mail or submitted an outbound reply.

workbin.email.in-progress.displayed-columns

- Default Value: From, Subject, Received
- Valid Values: A comma-separated list of Interaction Server interaction properties, for example: From, Subject, Received
- Changes take effect: When the application is started or restarted.
- Description: The list of interaction fields that are displayed as columns of the workbin that stores In-Progress e-mail interactions.

workbin.<media_type>.<nickname>

- Default Value: ""
- Valid Values: The name of a valid Script object of type Interaction Workbin.
- Changes take effect: When the application is started or restarted.
- Description: The name of the workbin that is to be used to store interactions of a particular media type. Agents can open interactions from this workbin but not save interactions in it.

workbin.<media_type>.<nickname>.displayed-columns

- Default Value: From,To,Subject,Received
- Valid Values: A comma-separated list of Interaction Server interaction properties, for example: From, Subject,Received
- Changes take effect: When the application is started or restarted.
- Description: The list of interaction fields that are displayed as columns of the specified workbin.

workbin.<media_type>.in-progress

- Default Value: ""
- Valid Values: The name of a valid Script object of type Interaction Workbin, that is owned by Agents.
- Changes take effect: When the application is started or restarted.
- Description: The name of the workbin to be used to store In-Progress workitems of the specified media type.

workbin.<media_type>.in-progress.displayed-columns

- Default Value: From,To,Subject,Received
- Valid Values: A comma-separated list of Interaction Server interaction properties, for example: From, Subject,Received
- Changes take effect: When the application is started or restarted.
- Description: The list of interaction fields that are displayed as columns of the specified workbin.