



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Developer's Guide

Windows

4/2/2025

Contents

- 1 Windows
 - 1.1 Learn about the Windows
 - 1.2 Close Windows
 - 1.3 Open and Restore Interaction Windows
 - 1.4 Manage Toaster
 - 1.5 Broadcast Window
 - 1.6 Additional GUI Commands
 - 1.7 References

Windows



Purpose: To provide information about customizable commands for the windows.
Updated in: 8.1.300.17

Learn about the Windows

The following commands apply to GUI components that your application can customize. For further information, see [Views and Regions](#), which lists the type of available components.

Read [Use Customizable Commands](#) to see code snippets which demonstrate the usage of the commands.

Close Windows

The following commands are used to close windows.

Chains of Commands to Close Windows

Default Commands	Parameters
Chain WindowClose	
<ul style="list-style-type: none"> IsPossibleToClose 	<ul style="list-style-type: none"> CommandParameter: <code>IIInteractionsWindow<ref name="IIInteractionsWindow" > Genesyslab.Desktop.Modules.Windows.Interactions.IIInteractionsWindow</code>
<ul style="list-style-type: none"> Close 	<ul style="list-style-type: none"> CommandParameter: <code>IIInteractionsWindow<ref name="IIInteractionsWindow" /></code>
Chain WindowInteractionClose	
<ul style="list-style-type: none"> IsPossibleToClose 	<ul style="list-style-type: none"> CommandParameter: <code>IIInteractionsWindow<ref name="IIInteractionsWindow" /></code>
<ul style="list-style-type: none"> Close 	<ul style="list-style-type: none"> CommandParameter: <code>IIInteractionsWindow<ref name="IIInteractionsWindow" /></code>

Open and Restore Interaction Windows

The following commands are used to screen-pop interaction windows.

Chains of Commands to Open and Restore Interaction Windows

Default Commands	Parameters
Chain RestoreInteractionsWindow Available since: 8.1.300.17	
<ul style="list-style-type: none"> RestoreInteractionsWindow 	<ul style="list-style-type: none"> CommandParameter: IInteractionsWindow<ref name="InteractionsWindow">Genesyslab.Desktop.Modules.Windows. Interaction: IInteraction<ref name="Interaction">Genesyslab.Desktop.Modules.Core.Model.Interaction. Case: ICase<ref name="ICase">Genesyslab.Desktop.Modules.Core.Model.Interactions.
Chain ShowInteractionsWindow Available since: 8.1.300.17	
<ul style="list-style-type: none"> ShowInteractionsWindow 	<ul style="list-style-type: none"> CommandParameter: IInteractionsWindow<ref name="IInteractionsWindow" /> Interaction: IInteraction<ref name="Interaction" /> Case: ICase<ref name="ICase" />

Manage Toaster

The following commands are available for the **Toaster Window**.

Chain of Commands to Manage Toaster

Default Commands	Parameters
Chain ShowToasterWindow Available since: 8.1.300.17	
<ul style="list-style-type: none"> ShowToasterWindow 	<ul style="list-style-type: none"> CommandParameter: IToasterWindow<ref name="IToasterWindow">Genesyslab.Desktop.Modules.Windows.View. Interaction: IInteraction<ref name="Interaction" />
Chain ToasterAcceptPreview	

Default Commands	Parameters
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: <code>Interaction<ref name="Interaction" ></code> <code>Genesyslab.Desktop.Modules.Core.Model.Interactions.Interaction</code>
Chain <code>ToasterDeclinePreview</code>	
<ul style="list-style-type: none"> Decline 	<ul style="list-style-type: none"> CommandParameter: <code>Interaction<ref name="Interaction" /></code>
Chain <code>ToasterInteractionAccept</code>	
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: <code>Interaction<ref name="Interaction" /></code>
Chain <code>ToasterInteractionDecline</code>	
<ul style="list-style-type: none"> Decline 	<ul style="list-style-type: none"> CommandParameter: <code>Interaction<ref name="Interaction" /></code> OtherDn: <code>String<ref name="String" ></code> <code>System.String</code> OtherDnLocation: <code>String<ref name="String" /></code>
Chain <code>ToasterInteractionEmailAccept</code>	
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: <code>InteractionOpenMedia<ref name="InteractionOpenMedia" ></code> <code>Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.InteractionOpenMedia</code> Extensions: <code>KeyValueCollection<ref name="KeyValueCollection" ></code> <code>Genesyslab.Enterprise.Commons.Collections.KeyValueCollection</code>
Chain <code>ToasterInteractionEmailDecline</code>	
<ul style="list-style-type: none"> Decline 	<ul style="list-style-type: none"> CommandParameter: <code>InteractionOpenMedia<ref name="InteractionOpenMedia" /></code> Reasons: <code>KeyValueCollection<ref name="KeyValueCollection" /></code> Extensions: <code>KeyValueCollection<ref name="KeyValueCollection" /></code>
<ul style="list-style-type: none"> Close <p>Available since: 8.1.200.16</p>	<ul style="list-style-type: none"> CommandParameter: <code>InteractionOpenMedia<ref name="InteractionOpenMedia" /></code>

Default Commands	Parameters
Chain ToasterInteractionIMAccept	
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: IInteractionIM<ref name="InteractionIM" > Genesyslab.Desktop.Modules.Voice.Model.Interactions.IInteract
Chain ToasterInteractionIMReject	
<ul style="list-style-type: none"> Reject 	<ul style="list-style-type: none"> CommandParameter: IInteractionIM<ref name="InteractionIM" /> RejectReason: String<ref name="String" /> Reasons: KeyValueCollection<ref name="KeyValueCollection" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> Reject 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="Interaction" />
Chain ToasterInteractionOpenMediaAccept	
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="InteractionOpenMedia" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" />
Chain ToasterInteractionOpenMediaDecline	
<ul style="list-style-type: none"> Decline 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="InteractionOpenMedia" /> Reasons: KeyValueCollection<ref name="KeyValueCollection" /> Extensions: KeyValueCollection<ref name="KeyValueCollection" />
<ul style="list-style-type: none"> Close Available since: 8.1.200.16 	<ul style="list-style-type: none"> CommandParameter: IInteractionOpenMedia<ref name="InteractionOpenMedia" />
Chain ToasterInteractionPreviewAccept	
<ul style="list-style-type: none"> Accept 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="Interaction" />

Default Commands	Parameters
	"Interaction" />
Chain ToasterInteractionPreviewDecline	
<ul style="list-style-type: none"> Decline 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="Interaction" />
Chain ToasterShowBroadcastMessage	
<ul style="list-style-type: none"> ShowToaster 	<ul style="list-style-type: none"> CommandParameter: IBroadcastMessage<ref name="IBroadcastMessage" />

Broadcast Window

These commands enable you to manage a broadcast message displayed to the agents.

Chain of Commands for the Broadcast Window

Default Commands	Parameters
Chain BroadcastMessageClose	
<ul style="list-style-type: none"> Close 	<ul style="list-style-type: none"> CommandParameter: String<ref name="String" > System.String</ref>
Chain BroadcastMessageShow	
<ul style="list-style-type: none"> Show 	<ul style="list-style-type: none"> CommandParameter: IBroadcastMessage<ref name="IBroadcastMessage" > Genesyslab.Desktop.Modules.Core.Model.Broadcast.IBroadcastMessage</ref> Source: BroadcastMessageWindowSource<ref name="BroadcastMessageWindowSource" > Genesyslab.Desktop.Modules.Windows.Views.Broadcast.BroadcastMessageWindowSource</ref>
Chain ShowMessageToasterWindow Available since: 8.1.300.17	
<ul style="list-style-type: none"> ShowMessageToasterWindow 	<ul style="list-style-type: none"> CommandParameter: IToasterWindow<ref name="IToasterWindow" /> BroadcastMessage: IBroadcastMessage<ref name="IBroadcastMessage" />

Additional GUI Commands

Additionally, you can use the following commands:

Additional Chains of Commands

Default Commands	Parameters
Chain ApplicationClose	
<ul style="list-style-type: none"> IsPossibleToClose 	
<ul style="list-style-type: none"> CloseAllInteractions 	
<ul style="list-style-type: none"> StopAllMonitoringCommand Available since: 8.1.300.17	
<ul style="list-style-type: none"> ChannelsLogOff Available since: 8.1.100.14	
<ul style="list-style-type: none"> NegotiatedLogout Available since: 8.1.100.14	
<ul style="list-style-type: none"> Close 	
Chain CancelConnectionCommand Available since: 8.1.300.17	
Chain NotepadInsertTimeStamp	
<ul style="list-style-type: none"> InsertTimeStamp 	<ul style="list-style-type: none"> CommandParameter: IInteraction<ref name="Interaction" /> TextBoxBase: TextBoxBase<ref name="TextBoxBase" >System.Windows.Controls.TextBoxBase</ref>
Chain PossibleToCloseAllInteractions	
<ul style="list-style-type: none"> IsPossibleToClose 	
Chain TeamCommunicatorAddToFavorite Available since: 8.1.200.16	
<ul style="list-style-type: none"> AddObjectTCToFavorite 	
Chain TeamCommunicatorModifyFavorite Available since: 8.1.300.17	

Default Commands	Parameters
<ul style="list-style-type: none">• ModifyFavorite	
Chain TeamCommunicatorOpenInteraction	
<ul style="list-style-type: none">• Open	<ul style="list-style-type: none">• ActionTarget: ActionTarget<ref name="ActionTarget" > Genesyslab.Desktop.Modules.Windows.Interactions.ActionTarget
Chain ContactIsModified	
<ul style="list-style-type: none">• IsModified	Caseld: String<ref name="String" />

References

<references />