



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workspace Desktop Edition Developer's Guide

SMS

12/17/2025

SMS

Purpose: To provide information about customizable commands.

Learn about SMS Commands

These commands manage operations on SMS interactions.

Important

Read [Use Customizable Commands](#) to see code snippets which demonstrate the usage of the commands.

Managing SMS Interactions

Chains of Commands to Manage SMS Interactions

Default Commands	Parameters
Chain InteractionSmsAccept	
Accept	CommandParameter: IInteractionSms - Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.Sms.IInteractionSms
Chain InteractionSmsCreateReplyMessage	
IsPossibleToCreate	SourcePhoneNumber: String - System.String
IsItPossibleToSendPageSms	OutboundQueue: String
SetContext	CorrelatorData: String

Default Commands	Parameters
Create	- CommandParameter: IMediaOpenMedia - Genesyslab.Desktop.Modules.OpenMedia.Model.Agents.IMediaOpenMedia - Subtype: String - ParentInteractionId: String(Enterprise Service ID) - SourcePhoneNumber: String - DestinationPhoneNumber: String - InputQueues: ICollection - System.Collections.Generic.ICollection - OutputQueues: ICollection - - UserData: KeyValueCollection - Genesyslab.Enterprise.Commons.Collections.KeyValueCollection - Extensions: KeyValueCollection - CorrelatorData: String
CreateUCS	EsdkInteraction: IInteraction - Genesyslab.Enterprise.Model.Interaction.IInteraction - ParentInteractionId: String
Chain InteractionSmsDecline	
Decline	- CommandParameter: IInteractionOpenMedia - Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.IInteractionOpenMedia - Reasons: KeyValueCollection - Extensions: KeyValueCollection

Default Commands	Parameters
Close	CommandParameter: IInteractionOpenMedia
Chain InteractionSmsDelete	
Confirm	- ActionToConfirm: String - ConfirmParentWindow: Window - System.Window.Window
IsContactModified	Caseld: String
Delete	CommandParameter: IInteractionOpenMedia
Chain InteractionSmsDisconnectSmsSessionChannel	
Disconnect	CommandParameter: IInteractionOpenMedia
Chain InteractionSmsGetHistoricMessage	
ExtractInteractions	- CommandParameter: String (contactId) - ListAttributes: StringList - Genesyslab.Platform.Contacts.Protocols.ContactServer.StringList - MediaTypes: String (list of media type seperated by comma.) - TimeFrame: System (time frame in hour) - ExcludedInteractions: IList<T> - System.Collections.Generic.IList<T> (interaction id) - InteractionsUCS: IList<T> (output parameter).

Default Commands	Parameters
DecodeInteractions	- InteractionsUCS: IList<T> - SmsMessages: ArrayList - System.Collections.ArrayList</ref>; the collection contains [ISmsMessage - Genesyslab.Desktop.Modules.Contacts.Decoder.Sms.ISmsMessage, output parameter].
Processing	- ModelView: ISmsViewModel - Genesyslab.Desktop.Modules.OpenMedia.Windows.Interactions.MediaView.Sms.InteractionMediaView - Interaction: Interaction - Genesyslab.Desktop.Modules.Core.Model.Interactions.Interaction - SmsMessages: ArrayList - System.Collections.ArrayList; the collection contains [ISmsMessage- Genesyslab.Desktop.Modules.Contacts.Decoder.Sms.ISmsMessage, output parameter].
Chain InteractionSmsIsPossibleToClose	
IsContactModified	Caseld: String
IsPossibleToClose	CommandParameter: IInteractionSms- Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.Sms.IInteractionSms
Chain InteractionSmsPlaceInQueue	
UpdateInteractionUCS	- CommandParameter: IInteraction - NotepadViewModel: INotepadViewModel

Default Commands	Parameters
IsContactModified	CasId: String
SaveAttachedData	- CommandParameter: IInteractionOpenMedia - UserData: KeyValueCollection
SetAutoClosePageMode	CommandParameter: IInteractionOpenMedia
PlaceInQueue	- CommandParameter: IInteractionOpenMedia - Destination: String - Reason: KeyValueCollection - Extensions: KeyValueCollection
SetAutoCloseSessionMode	CommandParameter: IInteractionOpenMedia
ReleaseParty	CommandParameter: IInteractionSms
AddRecentCall	RecentIndex: ObjectTC - Genesyslab.Desktop.Modules.TeamCommunicator.ObjectTC
Chain InteractionSmsSendMessage	
IsContactModified	CasId: String

Default Commands	Parameters
IsDispositionCodeMandatory	CommandParameter: IInteractionSms
SendMessage	- CommandParameter: IInteractionSms - Visibility: String - Message: String
MimizeWindow	- CommandParameter: IInteractionSms - Window: Window - InteractionContainerType: Genesyslab.Desktop.Modules.Windows.Views.Interactions.Container
Chain InteractionSmsSendMessage	
IsContactModified	Caseld: String
IsItPossibleToSendPageSms	OutboundQueue: String
Send	- CommandParameter: IInteractionSms - OutboundQueue: String - SourcePhoneNumber: String - Reason: KeyValueCollection - Extensions: KeyValueCollection - CorrelatorData: String

Default Commands	Parameters
UpdateInteractionUCS	CommandParameter: IInteraction
Chain InteractionSmsSendReplyMessage	
IsContactModified	Caseld: String
IsItPossibleToSendPageSms	OutboundQueue: String
Send	- CommandParameter: ISMSInteraction - Genesyslab.Enterprise.Model.Interaction.ISMSInteraction - OutboundQueue: String - Reason: KeyValueCollection - Extensions: KeyValueCollection - CorrelatorData: String
CloseParentInteraction	ParentInteraction: CommandParameter - CommandParameter
Chain InteractionSmsTransferAgent	
SetAutoClosePageMode	CommandParameter: IInteractionOpenMedia
RequestSaveNotepad	- CommandParameter: IInteraction - NotepadViewModel: INotepadViewModel - Genesyslab.Desktop.Modules.Windows.Interactions.INotepadViewModel

Default Commands	Parameters
TransferAgent	- CommandParameter: IInteractionOpenMedia - Destination: String - Reasons: KeyValueCollection - Extensions: KeyValueCollection
SetAutoCloseSessionMode	CommandParameter: IInteractionOpenMedia
ReleaseParty	CommandParameter: IInteractionSms
AddRecentCall	RecentIndex: ObjectTC
Chain InteractionSmsWorkflow	
PromptDone	- CommandParameter: IInteractionOpenMedia - ConfirmParentWindow: Window - System.Window.Window
ExitJoinIssue Available since: 8.5	- CommandParameter: Genesyslab.Desktop.Modules.OpenMedia.Model.Interactions.Sms.IInteractionSms - Reason: KeyValueCollection - Extensions: KeyValueCollection
ReleaseParty	CommandParameter: IInteractionSms

Default Commands	Parameters
UpdateInteractionUCS	CommandParameter: IInteraction
Workflow	- CommandParameter: IInteractionOpenMedia - Workflow: String - Reasons: KeyValueCollection - Extensions: KeyValueCollection
Commands common to all interactions	
Chain InteractionSetAttachedDataWithDelay	
SetAttachedData	- CommandParameter: IInteraction - AttachedData: KeyValueCollection
Chain BundleClose	
GetAttachedDataInformationUCS	CommandParameter: IInteractionsBundle - Genesyslab.Desktop.Modules.Core.Model.Interactions.IInteractionsBundle
UpdateNotePadForVoice	CommandParameter: IInteractionsBundle
ResetInteractionChatConsultation	CommandParameter: IInteractionsBundle
IsContactModified	Caseld: String

Default Commands	Parameters
IsPossibleToClose	CommandParameter: IInteractionsBundle
CompleteDispositionCodeOnBundle	CommandParameter: IInteractionsBundle
Close	CommandParameter: IInteractionsBundle
StopInteractionVoiceUCS	• CommandParameter: IInteractionsBundle
GetOutboundPreviewRecord	CommandParameter: ICampaign - Genesyslab.Enterprise.Model.Interaction.ICampaign