



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD Deployment Guide

Installing the iWD GAX Plugin

12/18/2025

Installing the iWD GAX Plugin

Contents

- [1 Installing the iWD GAX Plugin](#)
 - [1.1 Notes on Localization](#)
 - [1.2 Note on Removing the iWD GAX Plug-in](#)
 - [1.3 Note on Installing/Removing Language Pack Plug-ins](#)
 - [1.4 Upgrading Plug-ins from 8.5.0 to 8.5.1+](#)

iWD GAX Plugin is installed in the GAX standard way - the procedure is described [here](#) (opens a new document).

Important

Before any install of the GAX Plug-in, if you have installed it previously you must perform the removal procedure below to ensure a clean installation.

Notes on Localization

- The base GAX application and its plugins (including iWD GAX plug-in) are not fully separated with their localization.
- All localization packages of all supported plugins and the GAX base localization package should be installed together.
- All installed localization packages should contain the same set of languages.

Note on Removing the iWD GAX Plug-in

Important

If you perform the **GAX Plug-in removal procedure** for the iWD GAX Plug-in, you need to make sure that following files have been deleted (if you are working on Windows, some of these files might be already removed by the generic Windows uninstaller):

- <GAX_HOME>/webapp/WEB-INF/lib/gax-iwd.jar file
- <GAX_HOME>/plug-ins/gax-iwd.jar file
- <GAX_HOME>/webapp/plugins/gax-iwd directory

Note on Installing/Removing Language Pack Plug-ins

Important

Before you perform the **Installing Language Packs** procedure for any iWD GAX

Plug-in language upgrade or after you perform the **GAX Plug-in removal procedure** procedure for Language Pack removal, you need to make sure that following files have been deleted:

- `<GAX_HOME>/webapp/WEB-INF/lib/gax-iwd-lp-<lang-build>.jar` (for example, `gax-iwd-lp-de-de-8.5.100.02.jar` file -this should be removed by iWD GAX language pack uninstaller).
- `<GAX_HOME>/plug-ins/gax-iwd-lp-<lang-build>.jar` (for example, `gax-iwd-lp-de-de-8.5.100.02.jar` file).
- `<GAX_HOME>/webapp/plugins/gax-iwd-lp-<lang>` (for example, `gax-iwd-lp-de-de` directory).

Upgrading Plug-ins from 8.5.0 to 8.5.1+

To upgrade any plug-in, you need to follow the instructions above to remove the old plug-in, then install the new one.