



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD Data Mart Reference Guide

ETL_CUSTOM_MAP System

12/19/2025

ETL_CUSTOM_MAP System

The ETL_CUSTOM_MAP table is used to configure mapping of task custom attributes to attributes in the I_/H_TASK_FACT and I_/H_TASK_WORK_FACT tables, as well as the **CUSTOM_DIM dimension**.

The ETL_CUSTOM_MAP System Table

Field	Data Type	Description
ETL_CUSTOM_MAP_KEY	int	Unique mapping record key.
SOLUTION_KEY	int	Key to the SOLUTION dimension identifying the solution for which this mapping is valid. If NULL, the custom mapping applies to all solutions.
PROCESS_KEY	int	For which process this mapping is valid. If null applies to all processes.
DEPARTMENT_KEY	int	Key to the DEPARTMENT dimension .
TYPE	varchar(30)	Indicates where this custom attribute has been configured. One of the following: • taskattribute • taskdimension • tenant • department • process
KEY_NAME	varchar(255)	Custom attribute key name in the Interaction Server database.
IS_DIMENSION	int	Indicates whether this attribute should be mapped to the CUSTOM_DIM dimension instead of to a fact table. • 0 for taskattribute types • 1 for other than taskattribute types
CUSTOM_ATTRIBUTE_INDEX	int	Custom attribute index. If IS_DIMENSION is false (0), 0-9; otherwise 0-4.