



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Fetch filter

12/17/2025

Contents

- 1 Fetch filter
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Response Body
 - 1.4 Notes

Fetch filter

Method

GET

Syntax

GET /filters/<tenant_dbid>/<filter_name>

Response Body

```
{
  "name": "<filter name>",
  "owner": "<owner user name>",
  "public": <true/false>,
  "columns": [
    <column definition>,
    ...
  ],
  "criteria": [
    <criterion definition>,
    ...
  ]
}
```

Where:

- <column definition>:

```
{
```

Fetch filter

```
"category": "core/ext/data",
"name": "<attribute name>"
}
```

And:

- <criteria definition>:

```
{
  "template_expression": "<template_expression>",
  "template_key": "<template label key for i18n>",
  "elements":
  [
    {
      "type": "INPUT_INTEGER/INPUT_DATE/INPUT_TEXT/INPUT_ATTRIBUTE_NAME/INPUT_ATTRIBUTE_VALUE/PLAIN_TEXT",
      "name": "<element name>",
      "label": "<label key for i18n>",
      "value": "<current value>",
      "editable_list": <true/false>,
      "values":
      [
        {
          "value": "<available value>",
          "label": "<value label key>"
        },
        ...
      ]
    },
    ...
  ]
}
```

Notes

- values define a list of items that can be picked from a drop-down menu.
- A list of values is empty for elements of INPUT_DATE type. It can be non-empty for INPUT_TEXT and INPUT_INTEGER types. It is typically empty for INPUT_ATTRIBUTE_NAME and INPUT_ATTRIBUTE_VALUE - a list of available attributes and their values should be taken by a separate request (see:

Attributes). If the list of values exists and is not empty, it has precedence over the list of all attributes.

- Internal element types IS_IS_NOT, OPERATOR, TIME_UNIT, WAS_WAS_NOT, MORE_LESS, QUEUE are being converted to and from INPUT_TEXT with appropriate lists of values.
- `editable_list` indicates whether the element value input component is or is not editable, i.e. if a user is able to put a value out of the given list. For `INPUT_ATTRIBUTE_VALUE` the value of this property has precedence over the same property on the attribute definition.
- Labels for elements have a form of "CRITERION_LABEL_<CAPITALIZED_NAME>", for example `CRITERION_LABEL_IS_IS_NOT`.
- Actual labels for the criterion, elements and available values should be loaded from resources (localized). If there are not found, the element name should be used instead.
- `template_key` is a key to find a localized criterion template in resources. The localized template can contain parameters as element names in braces (for example `{attributeName}`). These parameters are replaced by either a proper input GUI component in edition mode or element's localized labels for displaying the criterion template. In case the `template_key` is not found in resources the criterion template is built of elements directly – one by one (elements of `PLAIN_TEXT` type – not used usually in localized templates – fill the text space then). All dynamic elements from `template_expression` must be included in the localized string to allow correct creation of a query string.
- `INPUT_ATTRIBUTE_VALUE` is an input element which data type should be dynamically determined basing on the type of attribute, chosen with `INPUT_ATTRIBUTE_NAME`, unless the element's values list exists and is not empty, because it has the precedence over the attribute values.
- `template_expression` is a legacy template expression, which is used here as the template criterion identifier only.
- A list of available columns is available under a separate address.