



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Fetch list of all available task attributes for Customer Filter Query in GTL

Contents

- 1 Fetch list of all available task attributes for Customer Filter Query in GTL
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Response Body
 - 1.4 Notes

Fetch list of all available task attributes for Customer Filter Query in GTL

Method

GET

Syntax

GET /gtl/attributes/<solution_dbid>

Response Body

```
[
  {
    "name": "<attribute name>",
    "column_label": "<localized column label>",
    "filter_label": "<localized attribute label used in filter conditions>",
    "type": "<string/date/int/img/list>",
    "values":
      [
        {
          "value": "<name or value>",
          "label": "<display name>"
        },
        ...
      ],
    "category": "core/ext/data",
    "filterable": true/false,
    "editable_list": true/false
    "column_name": "<column name used for mapping>"
  },
  ...
]
```

Notes

- The data format is the same for all the three types of requests, but the lists are different.
- Lists of attributes for filter definitions will be selected for a given tenant. Available values for "list" attributes are also tenant-specific.

- The list of attributes for Custom Filter Query in GTL is specific for a selected solution. Available values are also solution-specific.
- All the lists of attributes should be sorted by `filter_label` or `column_label`.
- All the lists of available values should be sorted by label.
- `filter_label` should be used to display the attribute in filter criteria and in customer filter query on GTL. `column_label` should be used to define a column in a filter. In most cases both labels are the same, but some attributes (of type date) should be displayed with different labels as a column title and in filter criteria. For example, "Activated D/T" and "Activated Date", respectively.
- `values` will be used only for the type "list". If true, a user should be allowed to type in a value that is not on the list.
- `editable_list` will be used only for the type "list".
- Attribute names are those used by iWD Manager internally (for example, `createdDateTime` and not `received_at`). They may differ from those used by Interaction Server. The database attribute names, defined in **Interaction Custom Properties/Values**/*<property>*/**annex/translation/translate-to**, should not be exposed by the API and will be used only internally to execute queries.
- `filterable` indicates if an attribute can be used in filter criteria or in Customer Filter Query. All attributes received in response to queries **/gtl/attributes** and **/filter/attributes** have `filterable` set to true. Some attributes received in response to the query **/filter/columns** have `filterable` set to false.
- `filter_label`, `column_label` and `column_name` can be used in Custom Filter Query in GTL: they all provide equal functional capabilities.