



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Fetch single task by task ID

12/14/2025

Contents

- 1 Fetch single task by task ID
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Response Body

Fetch single task by task ID

Method

GET

Syntax

GET /gtl/task/<solution_dbid>/<task_id>

Response Body

```
{
  "attribute_definitions":
  [
    {
      "name": "<attribute name>",
      "label": "<localized attribute label>",
      "type": "<string/date/int/img/list/age>",
      "category": "<core/ext/data>"
    },
    ...
  ],
  "task":
  {
    "core":
    {
      "<attribute_name>":
      {
        "value": <value>,
        "display_value": <display value>,
        "tooltip": <tooltip>,
        "missing": true
      },...
    },
    "ext":
    {
      ...
    },
    "data":
    {
      ...
    }
  }
}
```

- "data" attribute definitions are sorted ascending by the localized attribute label. "core" and "ext" attribute definitions are in the same order as they were in previous releases of iWD Manager.

- "age" type has the following format:

```
"value":  
{  
  "start": "<start_date_time>",  
  "end": "<optional_end_date_time>"  
}
```

- If "end" is present and not null, the UI should display the duration between "start" and "end". Otherwise, it should display the duration between "start" and the current time.
- The process, department and capturePoint attributes contain names of business structure objects found by IDs (RTID) from the task: processId, departmentId and capturePointId, respectively. If an ID is set in a task but the corresponding object is missing, the attribute value is set to a default value (RTID) and a flag—missing: true—is set for such an attribute. The UI should display the default value in a specific way; for example crossed out and with a localized tooltip. Example: The attribute is missing.
- "tooltip" and "display_value" are present only if different to the value. "display_value" is currently used only for channel.
- HTTP 404 Not Found if the task was not found.