iWD REST API Reference Guide

Get common task attributes for modification

4/29/2025

Contents

Get common task attributes for modification

Method

POST

Syntax

```
POST /gtl/tasks/common_data/<solution_dbid>?entity_dbid=<dbid>&entity_type=<department/
process/capturePoint/
solution>&filter=<filter_name>o_by=<qualified_attribute_name>o_direction=<ascending/
descending>&snapshot_id=<snapshot_id>
```

Request Body

Up to 9.0.012

Either:

```
{
        "include": [ <task_id1>, <task_id2>, ...]
}
```

Or:

```
{
        "exclude": [ <task_id1>, <task_id2>, ...]
}
```

From 9.0.013

Either:

```
{
    "content": {
        "include": [ <task_id1>, <task_id2>, ...]
    },
    "qlExpression": [<ql_item>, <ql_item>, ...]
}
```

Or:

```
{
    "content": {
        "exclude": [ <task_id1>, <task_id2>, ...]
    },
    "qlExpression": [<ql_item>, <ql_item>, ...]
}
```

Notes

- It is not allowed to send both "include" and "exclude" lists.

- snapshot_id is mandatory.

- The value for the **qlExpression** field is the same object as the request body from Fetch paginated list of tasks.

Response Body

```
{
  "attribute_definitions":
  [
    {
      "name": "<attribute name>",
      "label": "<localized attribute label>",
      "type": "<string/date/int/img/list>",
      "values":
       [
         {
           "value": "<name of value>",
           "label": "<display name>"
         },
         ...
      ],
      "category": "core/ext/data",
    },
    ...
  ],
  "attribute_values":
  {
    "core":
    {
        <attribute definitions>
    },
    "ext":
    {
        <attribute definitions>
    },
    "data":
    {
        <attribute definitions>
    }
  }
}
```

- "attribute_definitions" contains only editable attributes.

- "attribute_values" contains only attributes that have the same value for all the selected tasks.