



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Single task modification

Contents

- 1 Single task modification
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Request Body
 - 1.4 Response Body

Single task modification

Method

POST

Syntax

```
POST /gtl/task/solution_dbid>/<task_id>/modify
POST /gtl/task/solution_dbid>/<task_id>/modify_restart
```

Request Body

```
{
  "core":
  {
    "<attribute_name>":
    {
      "value": <value>
    },...
  },
  "ext":
  {
    ...
  },
  "data":
  {
    ...
  }
}
```

- Only modified attributes are included in the content.
- Attributes of type int—priority, businessValue—can have either a new numeric value, or a relative change, such as: +10, -5.

Response Body

Either:

HTTP/1.1 204 No Content

Or:

HTTP/1.1 200 Ok

plus:

```
[  
  <message>  
]
```

A warning message may be returned when the operation is successful, but an update to Universal Contact Server (UCS) failed. For example:

```
[ {  
  "severity" : "WARNING",  
  "message_id" : "CANNOT_OPEN_CONNECTION_TO_UCS",  
  "message" : "CANNOT_OPEN_CONNECTION_TO_UCS",  
  "args" : { }  
} ]
```