



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Interaction Server Administration Guide

Using the JMS Event Logger with TIBCO EMS

12/18/2025

Using the JMS Event Logger with TIBCO EMS

This example assumes the following:

- The host of the TIBCO message queue service is called **tibhost**.
- Queue called **event** is defined.
- Both user name and password are **guest**.
- The connection factory is called **tibconnectionfact**.

Configuring JMS Event Logger Application with TIBCO EMS

1. On the **Options** tab, create a section called **logger-settings**. In this section, add the following options:
 - `delivery-protocol =jms`
 - `delivery-queue-name =event` (the same as the queue name)
 - `username=guest`
 - `password=guest`
 - `jms-connection-factory-lookup-name=tibconnectionfact` (the name of the connection factory on TIBCO)
 - `jms-initial-context-factory=com.tibco.tibjms.naming.TibjmsInitialContextFactory`
 - `jms-provider-url=tibjmsnaming://tibhost:7222`
2. On the **Connections** tab of the Interaction Server which will use Event Logger, add connection to the just created Event Logger.
3. Configure the Interaction Server options to load JVM and all of the required libraries. Interaction Server Configuration for working with TIBCO is described in the [TIBCO—Interaction Server JVM](#) section of the [JMS Capture Point Guide](#).