



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Apple Messages for Business Guide

Apple Messages for Business Hub Driver Attributes

12/15/2025

Apple Messages for Business Hub Driver Attributes

The following is a list of attributes that the driver adds to the interaction.

Simple Text Message

Attribute	Type	Description
_umsMediaType	String	Always "applebc"
_umsMediaTypeChat	String	Always "applebcsession" value
_umsChannel	String	Channel name
_umsChatPossible	String	Always "true" value
_umsMsgId	String	Message identifier (Apple's data)
_umsMsgType	String	Always "text" value
_umsFromAddr	String	Unique identifier of Apple's user or "SYSTEM" for notification messages
_umsToAddr	String	Unique identifier of dialog (pair AppleUserId + businessId)
_umsConversationId	String	Unique identifier of dialog (pair AppleUserId + businessId)
_umsDriverDataWithAttachment	String	"False" for messages without attachment. "True" for messages with attachment.
_umsMsgPlainText	String	Text of message
_msg_PlainText	String	Text of message
Subject	String	Subject of message
_msg_CreatedAt	String	Timestamp for when message was received
_msg_MsgId	String	Message identifier (Apple's data)
_msg_MsgType	String	Always "text" value
_msg_FromUserId	String	Unique identifier of Apple's user
_msg_ToAddr	String	Unique identifier of dialog (pair AppleUserId + businessId)
_msg_ProfileServiceName	String	Always "ABC" value
_msg_ProfileUserId_ABC	String	Unique identifier of Apple's user

Attachment Message

Attribute	Type	Description
_umsMediaType	String	Always "applebc"
_umsMediaTypeChat	String	Always "applebcsession" value
_umsChannel	String	Channel name
_umsChatPossible	String	Always "true" value
_umsMsgId	String	Message identifier. Apple's data
_umsMsgType	String	Always "text" value
_umsFromAddr	String	Unique identifier of Apple's user or "SYSTEM" for notification messages
_umsToAddr	String	Unique identifier of dialog (pair AppleUserId + businessId)
_umsConversationId	String	Unique identifier of dialog (pair AppleUserId + businessId)
_umsDriverDataWithAttachment	String	"False" for messages without attachment. "True" for messages with attachment
_umsMsgPlainText	String	Text of message
_msg_PlainText	String	Text of message
Subject	String	Subject of message
_msg_CreatedAt	String	Timestamp of message receive moment
_msg_MsgId	String	Message identifier. Apple's data
_msg_MsgType	String	Always "text" value
_msg_FromUserId	String	Unique identifier of Apple's user
_msg_ToAddr	String	Unique identifier of dialog (pair AppleUserId + businessId)
_msg_ProfileServiceName	String	Always "ABC" value
_msg_ProfileUserId_ABC	String	Unique identifier of Apple's user
_umsDriverDataWithAttachment	String	Always "true" value
_umsDriverData	Binary	Information about attachment. Attachment Id, contentType, size