



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

[Cancel Invoked Session](#)

Cancel Invoked Session

The invoked SCXML session is cancelled if the invoking session exits the state where the invocation is made without waiting for an invocation-completion event, as shown in the sample below.

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:queue="www.genesyslab.com/modules/queue"
  xmlns:dialog="www.genesyslab.com/modules/dialog"
  initial="initial">
  <state id="initial">
    <transition event="interaction.added" target="invocation"/>
  </state>
  <state id="invocation">
    <invoke
      src="http://localhost:9090/strategies/01_BASIC/_aux/CheckInvokeCancel.xml"
      type="scxml"/>
    <transition event="invoked" target="routing"/>
    <transition event="error.invoke.invocation.*" target="error"/>
  </state>

  <state id="routing">
    <onentry>
      <queue:submit priority="5" timeout="20">
        <queue:targets type="dn">
          <queue:target name="'7102'"/>
        </queue:targets>
      </queue:submit>
    </onentry>

    <transition event="queue.submit.done" target="exit">
      <log expr="'DONE'"/>
      <log expr="_genesys.ixn.interactions[0].voice.ani"/>
      <log expr="'DONE'"/>
      <log expr="_event.data.targetselected"/>
    </transition>
    <transition event="error.queue.submit" target="error"/>
  </state>

  <final id="exit"/>
  <final id="error"/>
</scxml>
```