



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

[Create Call](#)

Create Call

The following SCXML strategy shows how to create a voice call with extension hints.

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:queue="www.genesyslab.com/modules/queue"
  xmlns:dialog="www.genesyslab.com/modules/dialog"
  xmlns:ixn="http://www.genesyslab.com/modules/interaction"
  initial="initial">
  <datamodel>
    <data ID="reqid"/>
    <data ID="ixnid"/>
    <data ID="time_delay" expr="'2s'"/>
  </datamodel>
  <state id="initial">
    <transition event="interaction.added" target="calling"/>
  </state>
  <state id="calling">
    <onentry>
      <log expr="'Calling ...'"/>
      <ixn:createcall requestid="_data.reqid" type="regular" from="'701'" to="'702'"
        udata="{key_1:10*10, key_2:20*20, key_3:30*30}" hints="{extensions:{key_1:100*100,
        key_2:200*200, key_3:300*300}}"/>
    </onentry>
    <transition event="error.voice.createcall" cond="_event.data.requestid == _data.reqid"
      target="error">
      <log expr="'Got createcall error:'"/>
      <log expr="uneval( _event )"/>
    </transition>
    <transition event="voice.createcall.done" cond="_event.data.requestid == _data.reqid"
      target="delay">
      <log expr="'Got createcall confirmation:'"/>
      <log expr="'event name = ' + _event.name"/>
      <script>
        _data.ixnid = _event.data.interactionid;
      </script>
    </transition>
  </state>
  <state id="delay">
    <onentry>
      <log expr="'==== Inside Delay ====='"/>
      <send event="'SynchroEvent'" delay="_data.time_delay"/>
    </onentry>
    <transition event="SynchroEvent" target="acceptcall"/>
  </state>
  <state id="acceptcall">
    <onentry>
      <ixn:accept requestid="_data.reqid" interactionid="_data.ixnid" resource="'702'"/>
    </onentry>
    <transition event="error.interaction.accept" target="error"/>
    <transition event="interaction.accept.done" cond="_event.data.requestid == _data.reqid"
      target="exit"/>
  </state>
  <final id="exit"/>
  <final id="error"/>
</scxml>
```