



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Orchestration Server Developer's Guide

Route to Agent Using Target ID

5/1/2025

Route to Agent Using Target ID

The following SCXML strategy routes an interaction to an agent, using the target id format.

```
<scxml version="1.0" xmlns="http://www.w3.org/2005/07/scxml"
  xmlns:queue="www.genesyslab.com/modules/queue"
  xmlns:dialog="www.genesyslab.com/modules/dialog"
  initial="initial">
  <state id="initial">
    <transition event="interaction.added" target="routing"/>
  </state>
  <state id="routing">
    <onentry>
      <queue:submit priority="5" timeout="20">
        <queue:targets>
          <queue:targetid expr="'az@.A'"/>
        </queue:targets>
      </queue:submit>
    </onentry>

    <transition event="queue.submit.done" target="exit">
      <log expr="'DONE'"/>
      <log expr="_genesys.ixn.interactions[0].voice.ani"/>
      <log expr="'DONE'"/>
      <log expr="_event.data.targetselected"/>
    </transition>
    <transition event="error.queue.submit" target="error"/>
  </state>

  <final id="exit"/>
  <final id="error"/>
</scxml>
```