



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Outbound Contact Deployment Guide

Dialing Modes and VoIP Deployment

4/2/2025

Dialing Modes and VoIP Deployment

An Outbound-VoIP environment supports all auto-dialing modes.

The following table provides a comparison of the modes in both a traditional and an IP environment.

Dialing Mode Comparison

Dialing Mode	Traditional	Outbound-VoIP - Ready
Predictive	Predictive	IP-predictive
Predictive GVP	Predictive	IP-predictive
Progressive	Progressive	IP-progressive
Predictive with seizing	Predictive ASM using CPD Server	IP-ASM (predictive)
Progressive with seizing	Progressive ASM using CPD Server	IP-ASM (progressive)
Power GVP	Power GVP using OBN	IP-VoiceXML (based on the calls per second setting)
Progressive GVP	Not applicable	IP-VoiceXML (based on port availability)

Configuration

Configuring Outbound Contact and SIP Server for a VoIP Deployment

Purpose

- To configure Outbound Contact and SIP Server so that a Campaign Group is *VoIP-Ready*.

Start

1. Configure a Trunk Group DN on the SIP Server switch object. For more information, see *Framework Genesys Administrator Help*.
2. Configure a Campaign Group object with the Trunk Group DN. For more information, see [Campaign Group Object](#).
3. Configure a SIP Server application object that controls the Trunk Group DN.
4. In the OCS application object, add this SIP Server on the Configuration tab/Connections section.

End