



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Engage Digital (eServices)

health-service

health-service

- `enable-keepalive`
- `log-output-timeout`
- `soap-accept-timeout`
- `soap-endpoint`
- `soap-hostname`
- `soap-receive-timeout`
- `soap-send-timeout`

enable-keepalive

Default Value: false

Valid Values: true, false

Changes Take Effect: After restart

This option specifies whether to keep a connection alive if the client requests the connection to be kept alive. If this option is set to false, a new connection will be opened each time a client sends a request to the web service.

log-output-timeout

Default Value: 0

Valid Values: Any integer from 0 to 600

Changes Take Effect: Immediately (after current interval)

An interval, in seconds, between periodic output of health counters into the log.

soap-accept-timeout

Default Value: 10

Valid Values: Any integer from 1 to 60

Changes Take Effect: After restart

An unfinished accept request would be aborted if it does not complete during the specified time interval.

soap-endpoint

Default Value: `http://{ServerName}:{ServerPort}/health`

Valid Values: Service endpoint

Changes Take Effect: After restart

The option specifies an endpoint template of the web service. The following keys in the endpoint template will be substituted if present: - {ServerName} – host name, either specified in the option 'soap-hostname' or equal to the hostname of the Interaction Server; - {ServerPort} – web service port, specified as "health" port of Interaction Server application; Default value: '`http://{ServerName}:{ServerPort}/health`'. Example: When 'soap-endpoint' is set to a default value, soap-hostname=myserver.mydomain.com and 'health' port in server ports list is 8088, the resulting endpoint will be: `http://myserver.mydomain.com:8088/health`

soap-hostname

Default Value:

Valid Values: A host name

Changes Take Effect: After restart

The option specifies the host name to be used for web service binding. If not specified or empty, the default value is the host name of the Interaction Server.

soap-receive-timeout

Default Value: 10

Valid Values: Any integer from 1 to 60

Changes Take Effect: After restart

An unfinished receive request would be aborted if it does not complete during the specified time interval.

soap-send-timeout

Default Value: 30

Valid Values: Any integer from 1 to 60

Changes Take Effect: After restart

An unfinished send request would be aborted if it does not complete during the specified time interval.