



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Engage Digital (eServices)

[index.contact](#)

index.contact

- **description**
- **enabled**
- **index-rebuild**
- **max-results**
- **storage-path**

description

Default Value: Contacts
Valid Values: Any character string
Changes Take Effect: At start/restart

This option specifies what will be sent to the Platform SDK contact client in response to a GetIndexProperties request.

enabled

Default Value: false
Valid Values: true, false
Changes Take Effect: At start/restart

Enables (true) or disables (false) the index.contact indexing service. If set to FALSE, the index.contact configuration section is ignored.

index-rebuild

Default Value: if-new
Valid Values: on-start, if-new, never
Changes Take Effect: At start/restart

Specified when the index will be rebuilt. A value of on-start indicates the index will be rebuilt each time UCS starts. A value of if-new indicates the index will be rebuilt on UCS startup if the index did not previously exist. A value of never means the index will never be rebuilt; only new/updated objects will be created.

max-results

Default Value: 10

Valid Values: Integer from 1 to 100

Changes Take Effect: At start/restart

Specifies the number of results returned by the search method of the index if the caller has not specified a maximum results value. If the caller has specified a value for the max-results parameter this option has no effect.

storage-path

Default Value:

Valid Values: Any valid system path

Changes Take Effect: At start/restart

Specifies the path to the directory in which the index service will create and store its files. For example, for the index section index.contact, and an option value of c:\data\, the full path to the files would be c:\data\index.contact. If Universal Contact Server is running on Unix or Linux, the option value should be set according to Unix naming rules. For example, setting the option value to /var/data for the index section contact.index indicates the files will be stored in the directory /var/data/index.contact.