

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Engage Digital (eServices)

scheduled-job-XX

# scheduled-job-XX

Options in this section are specific to the Context Services functionality of UCS.

action

enabled

period-type

cron-expression

period

#### action

**Default Value:** purge.service.closed **Valid Values:** See description **Changes Take Effect:** Immediately

Specifies the type of action to be performed when the pruning process runs.

- purge.service.all—Specifies that any started or completed services within the given time range will be purged.
- purge.service.open—Specifies that only non-completed services are purged from database.
- purge.service.open.anonymous—Specifies that only non-completed anonymous services are purged from database.
- purge.service.closed—Specifies that only completed services are purged from database.
- purge.service.closed.anonymous—Specifies that only completed anonymous services are purged from database.

#### cron-expression

**Default Value:** 0 0 20 ? \* 6L

Valid Values: Cron expression as described below.

Changes Take Effect: Immediately

Cron expression representing the scheduling.

More documentation about the syntax is at http://en.wikipedia.org/wiki/Cron.

The example expressed in the default value resolves to "schedule at 8pm on the last Friday of every

month".

#### enabled

**Default Value:** false **Valid Values:** true, false

**Changes Take Effect:** Immediately

Specifies if scheduled job should be taken into account.

### period

**Default Value:** 5

Valid Values: Any positive integer from 1 to 9999

Changes Take Effect: Immediately

Sets the time frame for pruning.

For example, if **period**=6 and **period-type**=days, then the job process will take a period of 6 days. See also the **period-type** option.

## period-type

**Default Value:** months **Valid Values:** See description **Changes Take Effect:** Immediately

#### Specifies the units to use for calculation of periods:

- hours—Specifies hours as the period calculation unit.
- · days—Specifies days as the period calculation unit.
- months—Specifies months (default) as the period calculation unit.
- years—Specifies years as the period calculation unit.

#### See also the **period** option.