

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services

openmedia or openmedia. < service-name > Section

openmedia or openmedia.<service-name> Section

These openmedia options enable you to configure the openmedia media used by the Digital Channel APIs. See Configuring Digital Channels for further details.

allow_overwrite

- interaction_subtype
- media_type

endpoint

interaction_type

allow overwrite

Default Value: false **Valid Values:** true, false

Changes Take Effect: Immediately

Introduced: 8.5.110.07

If true, enables Open Media API queries to overwrite the default Interaction Type, Subtype, and Media Type set in the Open Media service configuration. If you do not configure the options interaction_type, interaction_subtype, and media_type, you must set allow_overwrite to true and provide the Interaction Type, Subtype, and Media Type in your REST queries.

endpoint

Default Value: Environment:Default

Valid Values: <TenantName>:<InboundQueueName>

Changes Take Effect: Immediately

Introduced: 8.5.110.07

Any string that combines a valid Tenant Name and a valid Interaction Queue name, separated by a colon: <TenantName>:<InboudOueueName>

TenantName should match one of the Tenants assigned to the Interaction Server application.

interaction_subtype

Default Value: No default value

Valid Values: Any string

Changes Take Effect: Immediately

Introduced: 8.5.110.07

Interaction Subtype to assign to the interactions created by this service, for example, InboundNew. The Interaction Type must match one of the values listed in the **Business Attributes > Interaction Subtype** section of your configuration.

interaction_type

Default Value: No default value **Valid Values:** Any string

Changes Take Effect: Immediately

Introduced: 8.5.110.07

Interaction Type to assign to the interactions created by this service, for example, Inbound. The Interaction Type must match one of the values listed in the **Business Attributes > Interaction Type** section of your configuration.

media_type

Default Value: No default value

Valid Values: Any string

Changes Take Effect: Immediately

Introduced: 8.5.110.07

Media Type to assign to the interactions created by this service, for example, workitem. The Media Type must match one of the values listed in the **Business Attributes > Media Type** section of your configuration.