



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Voice Platform

CTI Connector

# CTI Connector

Options for this component are contained in the following configuration sections:

- CTIC
- ems
- ICMC
- IServer\_Sample
- IVRSC
- log
- mediacontroller
- sip
- Tenant1

## Tip

In the summary table(s) below, type in the Search box to quickly find options, configuration sections, or other values, and/or click a column name to sort the table. Click an option name to link to a full description of the option. Be aware that the default and valid values are the values in effect with the latest release of the software and may have changed since the release you have; refer to the full description of the option to see information for earlier releases.

**Power users:** [Download a CSV file](#) containing default and valid values and descriptions.

The following options are configured at the application level (in other words, on the application object).

| Section | Option                                      | Default   | Changes Take Effect |
|---------|---|---|---------------------|
| CTIC    | <a href="#">copy-originatingleg-headers</a> | X-Genesys-GVP-Session-Data  | After restart       |
| CTIC    | <a href="#">CTIFramework</a>                | IVRServerClient   | After restart       |
| CTIC    | <a href="#">DefaultDNIS</a>                 |   | After restart       |
| CTIC    | <a href="#">disable_cdr</a>                 | false   | After restart       |
| CTIC    | <a href="#">fips_enabled</a>                | False   | After restart       |
| CTIC    | <a href="#">GetDNISFromIServer</a>          | false   | After restart       |
| CTIC    | <a href="#">IVRPortBaseIndex</a>            | -1  | After restart       |
| CTIC    | <a href="#">MaxIVRPorts</a>                 | 2000  | After restart       |
| ems     | <a href="#">logconfig.MFSINK</a>            | <ul style="list-style-type: none"> <li>• <code> * *</code></li> </ul> | immediately         |
| Section | Option                                      | Default   | Changes Take Effect |

| Section        | Option                              | Default            | Changes Take Effect |
|----------------|-------------------------------------|--------------------|---------------------|
| ems            | logconfig.TRAPSINK                  | •  * *             | At start/restart    |
| ems            | trace_flag                          | FALSE              | immediately         |
| ICMC           | CancelResponseTimeoutMSec           | 2500               | After restart       |
| ICMC           | ConnectMsgTimeoutMSec               | 3500               | After restart       |
| ICMC           | DNISIndicator                       |                    | After restart       |
| ICMC           | eccSessionIdVarName                 | userSessionId      | At start/restart    |
| ICMC           | eccvariablelist                     | userSessionId:5000 | At start/restart    |
| ICMC           | enablePreRouting                    | false              | After restart       |
| ICMC           | ICMInterface                        | 0                  | After restart       |
| ICMC           | ICMUnavailableAction                | hangup             | At start/restart    |
| ICMC           | NewCallTimeoutMsec                  | 1500               | After restart       |
| ICMC           | RunScriptResultTimeoutMsec          | 2500               | After restart       |
| ICMC           | SessionIdleTimeoutMSec              | 120000             | After restart       |
| ICMC           | TransferOnDialogFailure             | false              | At start/restart    |
| ICMC           | translation-routed-call             | false              | After restart       |
| ICMC           | TrunkGroupID                        | 0                  | After restart       |
| IServer_Sample | cafile                              |                    | After restart       |
| IServer_Sample | certificate                         |                    | After restart       |
| IServer_Sample | clientname                          |                    | After restart       |
| IServer_Sample | enablekeepalivereq                  | 0                  | After restart       |
| IServer_Sample | iserveraddr                         |                    | After restart       |
| IServer_Sample | iserversocket                       |                    | After restart       |
| IServer_Sample | IVRSCClientPortRange                |                    | After restart       |
| IServer_Sample | keepalivereqinterval                | 5                  | After restart       |
| IServer_Sample | keepaliveresptimeout                | 3                  | After restart       |
| IServer_Sample | key                                 |                    | After restart       |
| IServer_Sample | noofkeepalivereqtosendinfailurecase | 3                  | After restart       |
| IServer_Sample | password                            |                    | After restart       |
| IServer_Sample | secured                             | false              | After restart       |
| IServer_Sample | type                                |                    | After restart       |
| IServer_Sample | verifydepth                         | 1                  | After restart       |
| IServer_Sample | verifypeer                          | false              | After restart       |
| IVRSC          | customeriserverslist                | IServer_Sample;    | After restart       |
| IVRSC          | fetchscriptidfromurs                | 0                  | After restart       |
| IVRSC          | scriptidkeyname                     |                    | After restart       |
| Section        | Option                              | Default            | Changes Take Effect |

| Section         | Option                               | Default  | Changes Take Effect  |
|-----------------|--------------------------------------|--|--|
| IVRSC           | WaitTimeforCallCreationInNetworkMode |  |  |
| log             | all                                  | ../logs/CTIConnector   | immediately  |
| log             | check-point                          | 1  | immediately  |
| log             | compatible-output-priority           | false  | immediately  |
| log             | debug                                | ../logs/CTIConnector   | immediately  |
| log             | expire                               | 20   | immediately  |
| log             | interaction                          | ../logs/CTIConnector   | immediately  |
| log             | keep-startup-file                    | false  | After restart  |
| log             | memory                               |  | immediately  |
| log             | messagefile                          |  | Immediately, if an application cannot find its *.lms file at startup |
| log             | message_format                       | short  | immediately  |
| log             | print-attributes                     | false  | immediately  |
| log             | segment                              | 10000  | immediately  |
| log             | spool                                |  | immediately  |
| log             | standard                             | ../logs/CTIConnector   | immediately  |
| log             | time_convert                         | local  | immediately  |
| log             | time_format                          | time   | immediately  |
| log             | trace                                | ../logs/CTIConnector   | immediately  |
| log             | verbose                              | standard   | immediately  |
| mediacontroller | codec_check_exclusion.payloads       |  | immediately  |
| mediacontroller | sdp.defaultipversion                 | true   | immediately  |
| mediacontroller | sdp.localhost                        | \$LocalIP\$  | immediately  |
| mediacontroller | sdp.localhost.ipv6                   | \$LocalIPv6\$  | immediately  |
| mediacontroller | suppress_bye_after_refer             | false  | immediately  |
| sip             | localuser                            | CTIConnector   | At start/restart   |
| sip             | mtusize                              | 1500   | After restart  |
| sip             | tcp.portrange                        |  | At start/restart   |
| sip             | tls.portrange                        |  | At start/restart   |
| sip             | transport.0                          | transport0<br>udp:any:5080   | At start/restart   |
| sip             | transport.1                          | transport1 tcp:any:5080  | At start/restart   |
| sip             | transport.2                          | transport2 tls:any:5081<br>cert=\$InstallationRoot\$/config/<br>x509_certificate.pem<br>key=\$InstallationRoot\$/config/<br>x509_private_key.pem | At start/restart   |
| Section         | Option                               | Default  | Changes Take Effect  |

| Section | Option                       | Default | Changes Take Effect |
|---------|------------------------------|---------|---------------------|
| sip     | transport.localaddress       |         | At start/restart    |
| sip     | transport.localaddress.srv   | false   | At start/restart    |
| sip     | transport.localaddress_ipv6  |         | At start/restart    |
| sip     | transport.routefailovertime  | 5       | At start/restart    |
| sip     | transport.routerecoverytime  | 30      | At start/restart    |
| sip     | transport.staticroutelist    |         | At start/restart    |
| sip     | transport.unavailablewakeupt | true    | At start/restart    |
| Tenant1 | Ports                        | 9000    | After restart       |
| Tenant1 | TenantName                   |         | After restart       |
| Section | Option                       | Default | Changes Take Effect |