



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

GatewayManager Section

12/18/2025

GatewayManager Section

- LocalSIPPort
- SessionTimerSupport
- UserAgentAddr
- SessionTimerSE
- TNZXferPrehangupWaitTime
- UserAgentPort

LocalSIPPort

Default Value: 5170

Valid Values:

Changes Take Effect: After restart

Specifies local SIP Port Number to be used by PSTN Connector for SIP Communication

SessionTimerSE

Default Value: 1800

Valid Values:

Changes Take Effect: After restart

The time interval in seconds which a call session must be refreshed, otherwise the session expires.

SessionTimerSupport

Default Value: true

Valid Values:

Changes Take Effect: After restart

Controls whether Session Timer support is enabled for a call session

TNZXferPrehangupWaitTime

Default Value: 4000

Valid Values:

Changes Take Effect: After restart

Time to wait before hangup after receiving the successful response for dialing digits

UserAgentAddr

Default Value:

Valid Values:

Changes Take Effect: After restart

When PSTN Connector receives a TDM call, this is the destination to which it will send the SIP call. Usually this would be the SIP Server IP Address

UserAgentPort

Default Value:

Valid Values:

Changes Take Effect: After restart

The destination Port Number for PSTN Connector on the SIP side. This would be SIP Server Port Number