



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

ems Section

ems Section

- `logconfig.MFSINK`
- `logconfig.TRAPSINK`

logconfig.MFSINK

Default Value:

- `|*|*`

Valid Values: Pipe delimited ranges for log levels, module IDs and specifier IDs. Ranges can be comma separated integers or range of integers or '*'.
Changes Take Effect: immediately

Controls the log messages that are sent to the MF sink. The format is 'levels|moduleIDs|specifierIDs' (repeated if necessary). The values between the pipes can be in the format: 'm-n,o,p' (ie "0-4, 5,6"). The wildcard character '*' can also be used to indicate all valid numbers. Example: '*|*|*' indicates that all log messages should be sent to the sink. Alternatively, '0,1|0-10|*|4|*|*' indicates that CRITICAL(0) and ERROR(1) level messages with module IDs in the range 0-10 will be sent to the sink; and all INFO(4) level messages will be sent as well.

logconfig.TRAPSINK

Default Value:

- `|*|*`

Valid Values:

Changes Take Effect: At start/restart

Specifies the metrics that are delivered to the SNMP Trap Sink.