



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

Tenant1 Section

Tenant1 Section

- **AccessGroup**
- **DialPrefix**
- **RPDN**
- **TGDN**

AccessGroup

Default Value:

Valid Values:

Changes Take Effect: After restart

The Access Group controls enabling of Digest Authentication for a tenant. The users configured under access group are allowed to send HTTP requests to SSG.

DialPrefix

Default Value:

Valid Values:

Changes Take Effect: After restart

The dial prefix, if present, will be prepended to all the target numbers. This applies to all outbound calls (across all IVR profiles) for the tenant. The dial prefix can be used, for example, to select a specific trunk in SIP Server or to select a specific ROUTE in PSTN Connector or to pass some predefined numbers to the switch (if the outbound call is going out via a switch) or any combination of these. Please see GVP User Guide for more details. This parameter is optional.

RPDN

Default Value:

Valid Values:

Changes Take Effect: After restart

The Routing Point DN is used by SSG to make outbound calls in case of Legacy GVP VXML Interpreter is used to play the IVR

TGDN

Default Value:

Valid Values:

Changes Take Effect: After restart

The Trunk Group DN parameter is used by SSG to fetch the resource information like available ports, total ports etc and also to make outbound calls in case of Next Generation VXML Interpreter is used to play the IVR. The tenant name is same as TGDN.