



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Interaction Concentrator

listeners Section

12/19/2025

# listeners Section

This section refers to a separate configuration section that describes the HTTP listening port. You must name this section **[listeners]** in the ICON Application. The name of this option must correspond to the section name for the **[user\_named\_section]** described below.

## Important

From release 8.1.512.08 forward, the functionality enabled in this section is no longer supported.

- **user-named-option**

## user-named-option

**Default Value:** No default value

**Valid Values:** Any string

**Changes Take Effect:** Immediately

**Important:** From release 8.1.512.08 forward, the functionality enabled by this option is no longer supported.

To enable access to the performance counters, configure an HTTP Listener option, and then configure a corresponding section, along with its **port**, **protocol**, and **transport** options.

- You must provide the name for any option you create in the **[listeners]** section. One option name must match the name of a new section you create to define the parameters for an http connection.
- Because ICON processes only the name of this option, but not the value, you can use the value to enter a short description for the connection; ICON prints this description to its log.

### Example:

```
[listeners]
http-9090="ICON HTTP listener"
```

Where http-9090 is the same as the name of the section that describes the parameters of an HTTP

connection at a port that ICON opens for listening.