



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# intelligent Workload Distribution

tomcat Section

## tomcat Section

- `accessLogDirectory`
- `accessLogEnabled`
- `accessLogPattern`
- `accessLogPrefix`
- `accessLogSuffix`
- `allowBackslash`
- `allowEncodedSlash`
- `connectionTimeout`
- `contextPath`
- `host`
- `jsDebugEnabled`
- `proxyName`
- `proxyPort`
- `proxySslEnabled`
- `proxySupportEnabled`
- `relaxedPathChars`
- `relaxedQueryChars`
- `serverName`
- `sessionTimeout`

### accessLogDirectory

**Default Value:** `/GCTI/iWD`  
**Valid Values:** Valid path to directory  
**Changes Take Effect:** After restart

Absolute or relative pathname of a directory in which access log files will be placed. If a relative path is specified, it is interpreted as relative to `$CATALINA_BASE`

### accessLogEnabled

**Default Value:** `false`  
**Valid Values:** `true` or `false`  
**Changes Take Effect:** After restart

Enables access logging

### accessLogPattern

**Default Value:** `common`  
**Valid Values:** Valid pattern code  
**Changes Take Effect:** After restart

A formatting layout identifying the various information fields from the request and response to be logged, or the word common or combined to select a standard format. Supported pattern codes are described on [https://tomcat.apache.org/tomcat-8.5-doc/config/valve.html#Access\\_Log\\_Valve](https://tomcat.apache.org/tomcat-8.5-doc/config/valve.html#Access_Log_Valve)

## accessLogPrefix

**Default Value:** iwd\_manager\_access  
**Valid Values:** Valid prefix for filename  
**Changes Take Effect:** After restart

The prefix added to the start of each log file's name.

## accessLogSuffix

**Default Value:** .log  
**Valid Values:** Valid suffix for filename  
**Changes Take Effect:** After restart

The suffix added to the end of each log file's name.

## allowBackslash

**Default Value:** true  
**Valid Values:** true or false  
**Changes Take Effect:** After restart

Allow encoded backslash in url.

## allowEncodedSlash

**Default Value:** true  
**Valid Values:** true or false  
**Changes Take Effect:** After restart

Allow encoded slash in url.

## connectionTimeout

**Default Value:** 60000  
**Valid Values:** Any integer from 0-86400000  
**Changes Take Effect:** After restart

The number of milliseconds this Connector will wait, after accepting a connection, for the request URI line to be presented. Use a value of -1 to indicate no (i.e. infinite) timeout

## contextPath

**Default Value:** /iwd\_manager

**Valid Values:** The valid context path

**Changes Take Effect:** After restart

Application context path.

## host

**Default Value:** 0.0.0.0

**Valid Values:** The valid host

**Changes Take Effect:** After restart

The host can either be a machine name or a textual representation of its IP address. Setting the host to 0.0.0.0 indicates that Server will be listening on all interfaces.

## jsDebugEnabled

**Default Value:** false

**Valid Values:** true or false

**Changes Take Effect:** After restart

Enables JavaScript debugging

## proxyName

**Default Value:** localhost

**Valid Values:** Valid server name

**Changes Take Effect:** After restart

Proxy server name

## proxyPort

**Default Value:** 80

**Valid Values:** Any integer from 1-65535

**Changes Take Effect:** After restart

Proxy server port

## proxySslEnabled

**Default Value:** false

**Valid Values:** true or false

**Changes Take Effect:** After restart

Indicates if proxy has SSL enabled

## proxySupportEnabled

**Default Value:** false

**Valid Values:** true or false

**Changes Take Effect:** After restart

Enables Proxy Support

## relaxedPathChars

**Default Value:**

**Valid Values:**

**Changes Take Effect:** After restart

Allows provided chars to be used in url path

## relaxedQueryChars

**Default Value:**

**Valid Values:**

**Changes Take Effect:** After restart

Allows provided chars to be used in url query

## serverName

**Default Value:** Apache

**Valid Values:** The valid server name

**Changes Take Effect:** After restart

Server name in response header

## sessionTimeout

**Default Value:** 60

**Valid Values:** Any integer from 0-1440

**Changes Take Effect:** After restart

Set the default session timeout (in minutes) for this web application