



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Workforce Management

auth Section

# auth Section

- `idp`
- `roles.administrator`
- `roles.supervisor`
- `provider`
- `roles.administrator.default`
- `roles.supervisor.default`

## idp

**Default Value:** empty

**Valid Values:** A short name representing the Identity Provider without spaces.

**Changes Take Effect:** After restart

**Dependencies:** [auth] provider

**Introduced:** 8.5.220.34

Enables Single Sign-On (SSO) using any external Identity Provider (IDP), supporting OpenID Connect, an industry-wide protocol. For more configuration details on the identity provider, see the knowledge base article [Workforce Management support for the Single Sign On SSO \(000109597\)](#). Note that the option **provider** in the **[auth]** section must have the value `wfm` for this functionality to work correctly.

## provider

**Default Value:** ""

**Valid Values:** "", `wfm`

**Changes Take Effect:** After restart

**Dependencies:** [Server] `tzdb`. See Important note in this option

**Introduced:** 8.5.214.08

Specifies the provider that performs WFM user authentication.

If this option value is set to:

- "" (empty string)—WFM Server SOAP API authenticates WFM users.
- `wfm`—WFM Server REST API (on-premises) authenticates WFM users. Such configuration influences default value of **tzdb** option which controls time zones usage.

### Important

When you see "" (empty string), this indicates that the option **Value** field should be

left blank. Also, if this option is set in one WFM Application, it must be set in all of them (WFM Web, WFM Server, WFM Builder, WFM Data Aggregator).

## roles.administrator

**Default Value:** " " (empty string)  
**Valid Values:** A string of characters  
**Changes Take Effect:** Immediately  
**Dependencies:** None  
**Introduced:** 8.5.218.

Specifies a comma-separated list of Genesys role names. (Do not add spaces between list items.) Users who are assigned any of these roles are designated as Administrators when they are auto-imported into the WFM database.

## roles.administrator.default

**Default Value:** " " (empty string)  
**Valid Values:** A string of characters  
**Changes Take Effect:** Immediately  
**Dependencies:** None  
**Introduced:** 8.5.218.

Specifies the name of WFM role that is assigned to the newly auto-imported administrator, if the user's Genesys role is not explicitly mapped to the WFM role.

## roles.supervisor

**Default Value:** " " (empty string)  
**Valid Values:** A string of characters  
**Changes Take Effect:** Immediately  
**Dependencies:** None  
**Introduced:** 8.5.218.

Specifies a comma-separated list of Genesys role names. (Do not add spaces between list items.) Users who are assigned any of these roles are designated as a supervisor when they are auto-imported into the WFM database.

## roles.supervisor.default

**Default Value:** " " (empty string)  
**Valid Values:** A string of characters  
**Changes Take Effect:** Immediately  
**Dependencies:** None

**Introduced:** 8.5.218.

Specifies the name of WFM role that is assigned to any newly auto-imported supervisor, if the user's Genesys role is not explicitly mapped to the WFM role.