



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Altocloud

pacingEndpoint Section

12/15/2025

pacingEndpoint Section

- `authClientId`
- `password`
- `authEndpoint`
- `targetEndpoint`

authClientId

Default Value: None

Valid Values: Valid client ID

Changes Take Effect: After server restart

Discontinued: 9.0.002

Client ID for premise-based customer, obtained from Predictive Engagement.

authEndpoint

Default Value: None

Valid Values: Valid URL

Changes Take Effect: After server restart

Discontinued: 9.0.002

HTTPS endpoint from which the OAuth2 token will be obtained.

To determine the correct domain name to access Genesys Predictive Engagement's public APIs, see [Regions](#).

An example of a target AuthEndpoint – public api endpoint is: <https://api.use2.genesys.cloud/api/v1/altocloud/oauth2/token>

password

Default Value: None

Valid Values: Valid *client_secret*

Changes Take Effect: After server restart

Discontinued: 9.0.002

client_secret for premise-based customer, obtained from Predictive Engagement.

targetEndpoint

Default Value: None

Valid Values: Valid URI path

Changes Take Effect: After server restart

The URI path specific for Pacing Service, with the default value in application template as **v2/journey/actiontargets/bulk**. This value will be combined with the parameter **base_service_url** of the **transaction object** in order to get the complete URL.