



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Engage Digital (eServices)

proxy Section

proxy Section

- `host`
- `port`
- `useProxy`
- `password`
- `socksVersion`
- `user`

host

Default Value:

Valid Values: Any alphanumeric string; for example: myProxyHost, 192.168.0.15

Changes Take Effect: At start/restart

Specifies the name or address of the host running the proxy. If not provided, an `IllegalArgumentException` is thrown. If E-mail Server is unable to connect to the host, a `MailConnectException` is thrown.

password

Default Value:

Valid Values: Any alphanumeric string

Changes Take Effect: At start/restart

Specifies the password to authenticate on the proxy (optional). If this option is present, "user" must also be present.

port

Default Value: 0

Valid Values: Any positive integer values less than 65535

Changes Take Effect: At start/restart

Specifies the port the proxy is running on. If the port number is absent or invalid, an `IllegalArgumentException` is thrown explaining the error.

socksVersion

Default Value: 5

Valid Values:

Changes Take Effect: At start/restart

Specifies the version of the SOCKS proxy in use. Common versions are 4, 4a, and 5. Defaults to 5.

useProxy

Default Value: false

Valid Values: true, false

Changes Take Effect: At start/restart

Enables (true) or disables (false) the proxy.

user

Default Value:

Valid Values: Any alphanumeric string

Changes Take Effect: At start/restart

Specifies the user name to authenticate on the proxy (optional). If this option is present, "password" must also be present.