



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Mobile Services

Reporting Section

4/22/2025

## Reporting Section

- `_rep_userevent_dn`
- `_rep_userevent_enable`
- `_rep_userevent_mediatype`
- `_rep_userevent_switch`

### `_rep_userevent_dn`

**Default Value:**

**Valid Values:** string

**Changes Take Effect:** Immediately

DN to which the reporting user event is sent. If `_rep_userevent_enable` is set to true, a value for this parameter is required.

### `_rep_userevent_enable`

**Default Value:** false

**Valid Values:** boolean

**Changes Take Effect:** Immediately

If set to true, the callback data is reported via user events to the switch and the specified DN (`_rep_userevent_switch` and `_rep_userevent_dn`).

**This option is mandatory.**

### `_rep_userevent_mediatype`

**Default Value:** 0

**Valid Values:** integer

**Changes Take Effect:** Immediately

Media type for the reporting user event generated from callback application. Accepts an integer value (ENUM) as per TLib specification for Media Types. Required when `_rep_userevent_enable` is set to true.

### Tip

This is an advanced parameter. To modify the value of an advanced parameter, you must enable **Advanced Parameters** in the Service Management UI.

## \_rep\_userevent\_switch

**Default Value:**

**Valid Values:** string

**Changes Take Effect:** Immediately

Switch to which the DN \_rep\_userevent\_dn belongs. Required if \_rep\_userevent\_enable is set to true.