



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Mobile Services

profiler Section

5/8/2025

## profiler Section

This section defines the collection and storage of operational metrics related to Context Services and Callback.

- [enable](#)
- [logged-classes](#)
- [stored-classes](#)

### enable

**Default Value:** false

**Valid Values:** true, false

**Changes Take Effect:** Immediately

**Introduced:** 8.5.112.05

Enables logging of profiled values and/or storage in Cassandra.

### logged-classes

**Default Value:** Empty string

**Valid Values:** String

**Changes Take Effect:** Immediately

**Introduced:** 8.5.112.05

Comma-separated list of classes that should print profiling information in the log. For example: "ServicesController,TasksController"

The list of supported classes is the following:

- AdminController
- CallbackController
- ServiceController
- ServicesCompositeController
- ServicesController
- StatesController
- StorageController

- TasksController

## stored-classes

**Default Value:** Empty string

**Valid Values:** String

**Changes Take Effect:** Immediately

**Introduced:** 8.5.112.05

Comma-separated list of classes that must store profiling information in the database. For example: "AdminController,TasksController"

The list of supported classes is the following:

- AdminController
- CallbackController
- ServiceController
- ServicesCompositeController
- ServicesController
- StatesController
- StorageController
- TasksController