



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services

request-access Section

request-access Section

- `_access_code_length`
- `_id`
- `_phone_number`
- `_provide_code`
- `_resource_group`

`_access_code_length`

Default Value: 6

Valid Values: Integer

Changes Take Effect: Immediately

Length of the access code which can be allocated. Note: Request parameter.

`_id`

Default Value: No default value

Valid Values: String

Changes Take Effect: Immediately

This option is mandatory.

Identifier of the service which the allocated access information should be associated with. Note: Request parameter.

`_phone_number`

Default Value: DNIS

Valid Values: String

Changes Take Effect: Immediately

This option is mandatory.

Phone number to associate with the reserved access information. Note: Request parameter.

_provide_code

Default Value: false

Valid Values: true, false

Changes Take Effect: Immediately

If set to true, the service returns an access code which will add more security and reliability when trying to correlate the incoming call with the service.

Note: Request parameter.

_resource_group

Default Value: DNIS

Valid Values: String

Changes Take Effect: Immediately

This option is mandatory.

Resource group from which an available access number will be taken. Note: Request parameter.