

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

mediacontroller Section

mediacontroller Section

- codec check exclusion.payloads
 sdp.localhost
- sdp.defaultipversion sdp.localhost.ipv6
- · suppress bye after refer

codec check exclusion.payloads

Default Value: 13 Valid Values:

Changes Take Effect: immediately

A list of space delimited payloads that will be excluded during codec checking for join result determination.

sdp.defaultipversion

Default Value: true Valid Values: ipv4, ipv6

Changes Take Effect: immediately

Default IP version to be used in SDP message, apply to initiated SDP offer to unjoined endpoint. Valid values are "ipv4" or "ipv6".

sdp.localhost

Default Value: \$LocalIP\$

Valid Values:

Changes Take Effect: immediately

The local host IPv4 address (only the host part) that will be used in SDP.

sdp.localhost.ipv6

Default Value: \$LocalIPv6\$

Valid Values:

Changes Take Effect: immediately

The local host IPv6 address (only the host part) that will be used in SDP.

suppress_bye_after_refer

Default Value: false

Valid Values:

- 1 Enable suppression
- **0** Disable suppression

Changes Take Effect: immediately

Suppress BYE after successful REFER. Turn on this feature if the call flow expects to receive BYE, this will avoid BYE messages from both direction.