



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Interaction Concentrator

dbw-error-reactions Section

12/20/2025

dbw-error-reactions Section

The option or options in this section define Interaction Concentrator reactions to specific database error messages. In other words, each configuration option in this section represents a rule for handling a certain database error.

If Interaction Concentrator receives a database error message, it tries to find the text specified in the configuration option as a substring of the error message. If it finds this substring text, it applies the specified error reaction.

You can use the predefined **uniqueness** error reaction or [configure your own options](#).

- [uniqueness](#)

uniqueness

Default Value:

Valid Values: Any string in the format error=error_substring;reaction=reaction_type

Changes Take Effect: Immediately

Defines how ICON reacts to a database error message that contains a particular text substring. Create a separate option for every database error message for which a certain reaction is required. Specify any meaningful name as the option name, making it unique within the dbw-error-reactions section; ICON does not process the name parameter. Include both a database error message and the expected reaction as two parameters of the option value, in the following format: error=<error substring>;reaction=<reaction type>

Example: error=unique;reaction=ignore

For more information about the syntax of the error substring and supported reaction types, see the description of this option in the *Interaction Concentrator Deployment Guide*.